

## **75396 Desert Skiff & Sarlacc Pit**

Adapted by Jordi Isus. Tested by Jolene Nemeth.

Replay a thrilling Star Wars: Return of the Jedi scene and create new adventure stories with this LEGO® brick-built Desert Skiff & Sarlacc Pit toy vehicle playset (75396) for kids aged 9 and over. The desert skiff features translucent elements for a hover effect and has playful details such as a push-out plank for Luke Skywalker to walk and the foldout railing where Han Solo nearly fell off. The pit has to move the Sarlacc's tentacles, and the Sarlacc has space in its mouth for a LEGO minifigure.

A cool gift for boys, girls and any fans of the classic Star Wars™ saga, this collectible toy building set has 6 LEGO minifigures, including Luke Skywalker, Han Solo, Chewbacca, Lando Calrissian and Boba Fett, plus authentic accessories. The other character in the set is a special LEGO Star Wars 25th anniversary minifigure of Nien Nunb.

Sarlacc pit – Features levers to move Sarlacc's tentacles and Sarlacc's mouth opens and has space for a LEGO® minifigure inside

Buildable LEGO® Star Wars™ toy vehicle – The desert skiff features translucent elements for a hover effect, a plank for Luke Skywalker to walk and the breakaway railing where Han Solo nearly fell off

Gift for kids aged 9 and over – This collectible toy building set makes a fun gift for boys, girls, fans of the classic Star Wars™ saga and Star Wars collectors

Intuitive instructions – Using the LEGO® Builder app, kids can zoom, rotate, and visualize a digital version of the construction models as they build

LEGO® Star Wars™ sets for all ages – LEGO Star Wars building toys let kids and adult fans relive iconic scenes, create new adventure stories, or simply display the brick-built models

Build, play and display – The Sarlacc pit buildable model in this 558-piece LEGO® Star Wars™ set measures over 9 cm (3.5 in.) high, 22 cm (8.5 in.) wide and 13 cm (5 in.) deep

The front of the box shows a desert scene, with a floating desert skiff above the Sarlacc pit and minifigures of Boba Fett, Luke Skywalker, Han Solo, Chewbacca, and Lando Calrissian! In the bottom left corner, there's a special logo celebrating 25 years of LEGO Star Wars, plus an exclusive Nien Nunb minifigure!

The back of the box has pictures showing how the set works. It has the Sarlacc pit, which has brown tentacles that move. There's also the desert skiff, a floating ship. One picture shows that part of the ship can lift or open. Another picture shows the skiff placed over the Sarlacc pit, like in the movie. There are 4 minifigures: Luke Skywalker, Han Solo, Chewbacca, and Boba Fett. They can stand on the skiff or near the pit. One picture shows Boba Fett falling into the pit, so you can play out the scene!

At the bottom, there's the LEGO Star Wars website and the Disney logo. The background looks like the desert of Tatooine!

This set contains 558 pieces in total and is for ages 9+.

This set comes with 6 bags labeled 1-6, 2 instruction books, and some loose pieces.

Bag 1 includes the pieces for Boba Fett and the Sarlacc pit.

Bag 2 includes the pieces for Lando Calrissian and the Sarlacc pit.

Bag 3 includes the pieces for Luke Skywalker and the Sarlacc pit.

Bag 4 includes the pieces for Hans Solo and the Sarlacc pit.

Bag 5 includes the pieces for Chewbacca and the desert skiff.

Bag 6 includes the pieces for LEGO Star Wars 25th anniversary minifigure of Nien Nunb and the desert skiff.

Welcome to text-based instructions from Bricks for the Blind. Before you start building, here are some terms we'll be using:

- In Front of/Front: towards you.
- Behind/Back: away from you.
- Up: towards the ceiling.
- Down: towards the floor.
- Stud: the bump on a LEGO brick. Example: A 2x1 brick has two studs on it.
- Vertically: with the longest side going from front to back
- Horizontally: with the longest side going from left to right.
- Upright: pointing up towards the ceiling.
- Standing upright: The piece is perpendicular to the ground, like a wall.
- Lying flat: The piece is parallel to the ground, like a piece of toast which fell off the table.
- That one/ppp: previously placed piece.
- Plate: piece with studs.
- Tile: smooth piece without studs (unless otherwise specified)
- A jumper plate is a 1x2 plate with a single stud on top, or a 1x3 plate with only two studs on top.
- "Anti-stud" is a term for the portion of a LEGO piece which accepts studs, like the bottom of a plate or brick.
- Symmetrically: a mirror image. Example: If you place a 2x1 brick with technic connector on the front wall at the right, connector to the front, and then place another such piece symmetrically on the back wall, at the right, the technic connector of the second piece should point to the back, since it will be placed symmetrically.
- Centered-vertically: even amount of space in front of and behind piece
- Centered-horizontally: even amount of space left and right of piece.
- Row: studs lined up horizontally (left to right/side to side).
- Column: studs lined up upright or vertically (top to bottom/back to front).

A note on LEGO Technic™ part names. These parts are somewhat different from regular LEGO bricks. Here are some definitions in case the builder or helper is not familiar with LEGO Technic™.

- Axles - An axle is a connector which has an X shaped cross-section. Because their cross section is not round, anything connected to an axle using an axle-hole will rotate with that axle. Axles are longer than they are wide, and the length of an axle corresponds with how many bricks long it is. Aka a 3L axle is three bricks long. Axles come in a variety of lengths, with a 2L axle being the shortest available. They may be combined with pins or have circular stops on them. A stop prevents the axle from sliding through an axle-hole at a specific point on the axle.
- Pins - A pin is a connector which has a circular cross section and a flanged notch out of one or both ends. This flanged notch allows them to click into bricks with a pinhole. Pins come with and without friction ridges, which are small bumps on the pin which prevent them from rotating freely. For standard pins, black is a high friction pin, and gray is a low friction pin. A standard-length pin is two brick lengths long, with a stop in the middle. This prevents a brick from being pushed from one side of the pin to the other. A 1L pin is one brick long and still retains the stop; however, it also includes a hollow stud at the other end. A 3L pin is three bricks long, and only contains a stop at one side, allowing two bricks to be pushed onto the other side of the pin. Pins may also have one side which is an axle.
- Technic brick - a brick which contains one or more holes which accept technic pins.
- Lift-arms - A lift-arm is a basic structural element, similar to a brick or a plate, but usually without any studs. It is a beam with rounded ends and with holes in it, with the same spacing as the studs on a LEGO brick. lift-arms come in a variety of lengths, including a 1x1 lift-arm which looks like a cylinder. Thick lift- arms are as wide as a LEGO brick, and thin lift-arms are half as wide as a LEGO brick, but not the same thickness as a LEGO plate! The holes in a lift-arm arm may accept axles or pins. They also come in a variety of shapes, including tees, ells, and triangles.
- Gears - A gear is a functional element. They are typically discs with teeth on the outside; there are also worm gears which look like a spiraling cylinder! Gears connected by axles transmit or even transform rotational motion!
- Axle and Pin Connectors - These elements are typically smaller than lift-arms and are used to connect some combination of pins or axles. They might have pins or axles, as well as axle or pinholes. They have a lot of different angle combinations! The simplest just connects two axles or pins together in a straight line.
- Bushes/Bushings - LEGO Technic™ uses bushes largely as spacers, but they also can reduce friction between rotating parts or can form useful elements such as bars. Bushes are typically light gray, cylindrical, and have an axle-hole running through the middle. They have a flange at the front and back to make it easier to pull on and off.

For builders with low vision, or a sighted building partner who may want to follow along with the printed visual instructions that come with each kit, PDF versions are always online at LEGO.com: (<https://www.lego.com/en-us/service/buildinginstructions/75396>) As low vision users may benefit from viewing the instructions on a personal device where they can zoom in on content and use assistive technologies to enhance the visuals.

Sorting the pieces:

To begin a successful build, it helps to sort the pieces into groups, bags, or small containers. Have a sighted friend or family member do this in advance following the instructions below. You will see that the pieces should be sorted into groups according to the building steps in the set. Doing this in advance makes locating the pieces easier. See below on how to sort the pieces to

correspond to the steps in this set. Number the containers using letters A-Z, Numbers or meaningful names. The parts will be collected into a small Number from steps in the instructions. Example: Steps 1-3 means collecting all the parts used in steps 1, 2 and 3, and putting them in one container.

This set comes with 6 bags labelled 1-6 and 2 instruction booklets. The first instruction booklet contains the instructions to build the Sarlacc Pit, and the second instructions booklet contains the instructions to build the Desert Skiff. Note that the steps begin again from 1 upon completion of each main build.

Sort the pieces into groups as described below. Note that where there are multiple colors of the same brick in a step, the colors will be split across two groups to make telling the difference easier for the builder!

LEGO includes a few spare parts in case you lose something. Set these into their own group away from the rest, in case you need them later.

Specific guidelines on column and row references:

The 2 builds have a unique shape, the Sarlacc pit almost like a volcano and the desert skiff like a spaceship, so clear placement is key for a smooth experience. To help you follow the instructions easily, here are a few important placement guidelines:

- Rows and Columns: Unless we say otherwise, rows and columns are counted across the whole build.
- Choosing Columns: If a part spans more than one row, use the row with more columns to decide where to place it. Vertically place a nougat 1x2 curved left slope wedge tile on the 4th and 5th rows from the back on the 4th and 5th columns from the left, so it slopes to the front. If the 4th row is longer, it has more columns, we will count the 4th row for the column reference.

Visible columns and rows of studs as Reference: When tiles or slopes make the counting of the entire build difficult, we will count only the visible columns and rows. Example: Place a dark tan 2x2 plate on the 3<sup>rd</sup> and 4<sup>th</sup> columns of studs from the left of the 3<sup>rd</sup> and 4<sup>th</sup> rows of studs from the front. In this case, ignore rows that are fully covered and count only the rows where studs are visible. Do the same with the columns.

#### Placement by Column

We might ask you to place parts on specific rows within a column. This is helpful when columns have different depths. Example: Place a tan 2x2 plate on the 2 back rows of the 3rd column from the left. Go to the 3rd column from the left. Count how many rows deep that column goes. In this case, place the plate on the last two rows of that column—those closest to the back edge. Each column might have a different depth, so always count rows within the column itself.

#### Placement by Row

Other times, we'll describe placement by referencing columns within a specific row. This helps when rows vary in width. Example: Place a dark gray tile on the 2 rightmost columns of the 4th row from the front. Go to the 4th row from the front. Count how many columns wide that row is. In this case, place the tile on the last two columns of that row—those furthest to the right. Each row may have a different width, so always count columns within the row itself.

Book 1: Sarlacc Pit

Bag 1

Group 1: Boba Fett pages 6 and 7.

Group 2: contains the pieces for steps 1-4.

Group 3: contains the pieces for step 5.

Group 4: contains the pieces for steps 6-14.

group 5: contains the pieces for steps 15-20.

group 6: contains the pieces for steps 21-23.

Bag 2

group 7: Lando Calrissian page 34.

group 8: contains the pieces for steps 24-30.

Group 9: contains the pieces for steps 31-35.

Group 10: contains the pieces for steps 36-42.

Bag 3

Group 11: Luke Skywalker page 60.

Group 12: contains the pieces for steps 43-53.

Group 13: contains the pieces for steps 54-62.

Group 14: contains the pieces for steps 63 and 64.

group 15: contains the pieces for steps 65 and 66.

Bag 4

Group 16: Hans Solo page 86.

Group 17: contains the pieces for steps 67-70.

Group 18: contains the pieces for steps 71-78.

Group 19: contains the pieces for steps 79-83.

Book 2: Desert Skiff

Bag 5

Group 20: Chewbacca page 2.

Group 21: contains the pieces for steps 1-7.

Group 22: contains the pieces for steps 8-18.

Group 23: contains the pieces for steps 19-22.

group 24: contains the pieces for steps 23-25.

Bag 6

Group 25: Nien Nunb 25th anniversary minifigure pages 36 and 37.

Group 26: contains the pieces for steps 26-38.

Group 27: contains the pieces for steps 39-47.

Group 28: contains the pieces for steps 48-64

Group 29: contains the pieces for steps 65-75.

Let's get to building!

Building Instructions (Bag 1, Book 1):

Group 1 – Boba Fett

Sub-build 1: Locate a pair of light blue legs printed with armor details, a yellow and gray torso printed with straps, pockets, and a small emblem on the left side of the chest, a tan head printed with a battle-ready expression, a green helmet printed with black and red details, including a black T-shaped visor marked with red war symbols, a black rangefinder antenna, a green jetpack, a black rifle and a barrel. Assemble the minifigure, before attaching the head, Attach the hole of the jetpack to the neck pin so the jetpack faces the back. Next, attach the head and position the helmet so the visor covers the face with the part that hangs down at the front. Insert the antenna into the hole in the right side of the helmet. Finally, assemble the rifle, attach the barrel to the lower pin of the weapon, and place the handle of the rifle in Boba Fett's right hand. Now he's ready for action! Set the minifigure aside while we start building the Sarlacc pit.

Sarlacc Pit

Group 2:

1. Vertically place a Black 4x10 plate in front of you. Then place a black 2x2 inverted slope brick on the back row so it is centered horizontally and slopes and overhangs to the back.
2. Place another black 2x2 inverted slope brick to the left of the ppp so it overhangs 1 column to the left and 1 row to the back. It should slope upwards to the back.
3. Vertically place a black 4x10 plate under the left overhang so it aligns with the previous 4x10 plate.
4. Place a black 2x2 inverted slope brick on the second and third columns from the left on the back row so it slopes and overhangs to the back.

Then place a brown 2x2 tile on the 3<sup>rd</sup> and 4<sup>th</sup> rows from the front so it is centered horizontally.

Group 3:

- 5.1 Let's make a part! Horizontally place a nougat 1x2 plate in front of you. Then place a black 1x2 plate with 2 clips on the long side on the ppp so the clips point to the front, and the hands of the clips face up and down.
- 5.2 Stack 2 nougat 1x2 plates. then place them horizontally on top of the ppp.
- 5.3 Place the 1x2 plate of a black 2x2 tile with upright 1x2 plate horizontally on the ppp so the anti studs face the back. Then place a black 1x2 plate with 2 clips on the long side horizontally on the ppp so the clips face the front, and the hands of the clips point up and down.
- 5.4 Horizontally place a nougat 1x2 log brick on the ppp. Then place the 1x2 plate of a black 2x2 tile with upright 1x2 plate horizontally on the ppp so the antistuds face the back.
- 5.5 Hold the sub build upright and attach the 1x2 plate of a black 2x2 tile with upright 1x2 plate horizontally under the build so the anti studs face the back.

5.6 Flip the sub build so the clips face up. Then turn the sub build 90 degrees clockwise so the hands of the clips point left and right. In this position place it on the main build on the 5<sup>th</sup> and 6<sup>th</sup> rows from the front so it is centered horizontally. The side with antistuds should face the left.

Group 4:

6. Let's make a part! Place a black 1x12 brick with 11 holes horizontally in front of you.

7.1 Let's make 2 identical parts! Place a gray 9L axle horizontally in front of you. Then attach a gray 3L axle connector to the right end of the ppp. Then insert a red 2L axle into the right facing axle hole. You should now have 2 identical parts.

7.2 Attach the left axle hole of a grey 1x2 liftarm with pin and axle hole to the red 2L axle of the first part. Repeat with the second part. They are the levers.

7.3 Vertically attach the 9l axel of your part to the second back facing pinhole from the left so the liftarm faces the back and the pin hole of the liftarm faces the right.

Repeat symmetrically to the right.

8. Push a black bush through the front right facing axle so it goes all the way in. Repeat symmetrically to the left.

9.1 Let's make 2 identical parts! Stack 2 2l thin lift arms with axel holes horizontally in front of you. Insert the axel of a brown pin connector into the right axel hole so the pin hole faces left and right. Flip your part on its side so the pin connector faces the back right. Attach the left axel hole of your part to the left front facing axel of your sub build so the pin connector is in the back and on the right. Make sure it goes all the way back and touches the bush. The pin hole should face the right. You should now have 2 identical parts!

10. Push a black 2L pin connector through the front right facing axle. the Vent hole should face right. Repeat symmetrically to the left.

11.1 Let's make 2 identical parts! Stack 2 2l thin lift arms with axel holes horizontally in front of you.

Insert the axel of a brown pin connector into the right axel hole so the pin hole faces left and right. You should now have 2 identical parts.

11.2 Flip the 1<sup>st</sup> part on its side so the pin connector faces the back right. Attach the left axel hole of your part to the left front facing axel of your sub build so the pin connector is in the back and on the right. Make sure it goes all the way back and touches the bush. The pin hole should face the right.

11.3 Attach the 2<sup>nd</sup> part symmetrically to the right facing axle of your sub build.

12. Push a black bush onto the right front facing axle so it goes all the way back. Repeat symmetrically to the left.

13. Let's secure the sub build! Horizontally attach a black 1x10 brick with 9 holes to the 2 front facing axels. The left axel should go into the leftmost back facing hole of the brick and it should be symmetrically attached on the right. Make sure the structure you have built before doesn't change its position as it wouldn't work later.

14. Keeping the same orientation, place your part on the build so it is centered horizontally and the 1x12 brick sits in front of the 2x2 inverted slope bricks and the 1x10 brick is on the second row from the front. The 1x12 brick should overhang 2 columns to the left and right. The 1x10 brick should overhang by 1 column to the left and right. The levers should protrude to the back.

Group 5:

15. Vertically place a black 6x10 plate under the left overhang so it aligns with the 4x10 plate. Repeat symmetrically to the right.

16. Let's make a part! Horizontally place a tan 2x12 plate in front of you. Then place a gray 1x2 inverted slope brick underneath the leftmost column so it slopes to the back. place another symmetrically to the right. Horizontally place your part on the back 2 rows so it is centered horizontally and slopes to the back. The 2x12 plate should sit on the 2x2 inverted slope bricks.

17. Horizontally place a black 2x4 brick on the back 2 rows of the 4 leftmost columns. Then horizontally place another in front of the ppp. Repeat both parts symmetrically to the right.

18. Horizontally place a gray 2x4 brick on the front row on the 6<sup>th</sup> through 10<sup>th</sup> columns from the left. It should overhang 1 row to the front. Place a gray 2x6 brick horizontally to the right of the ppp.

19. Horizontally place the 2 rightmost columns of the back row of a tan 4x8 plate under the left front overhang so it aligns with the left side of the build. Repeat symmetrically to the right.

20. Vertically place a grey 1x3 brick on the 4<sup>th</sup> 5<sup>th</sup> and 6<sup>th</sup> rows from the front on the 5<sup>th</sup> column from the right. Repeat symmetrically to the left.

Group 6:

21.1 Let's make a part! Horizontally place a tan 4x6 plate in front of you. Horizontally place a dark tan 2x4 brick on the 2 front rows so it is centered horizontally.

21.2 Vertically place 2 gray 2x6 bricks behind the ppp. They should overhang 4 rows to the back.

21.3 Vertically place a tan 2x6 brick to the left of the ppps so it overhangs 4 rows to the back and 1 column to the left.

21.4 Place a tan 3x3 wedge plate with cut off corners in front of you so the right angle faces the back right. Now place the back 2 rows of the rightmost column of the plate under the front 2 rows of the left overhang so the left 2 columns of the back row are exposed.

21.5 Horizontally place a tan 1x2 brick on the back row of the ppp. Horizontally place a tan 1x2 slope tile on the 2 left columns of the 2<sup>nd</sup> row from the front so it slopes to the front.

21.6 Rotate the sub build 90 degrees clockwise. Then Attach it to the left of the main build on the 4 left columns on the 5<sup>th</sup> through 10<sup>th</sup> rows from the front.

22.1 Let's make a part! Place a tan 4x6 plate horizontally in front of you. Then horizontally place a tan 2x4 slope brick on the front 2 rows so it is centered horizontally and slopes to the front.

22.2 Vertically place 2 gray 2x6 bricks behind the ppp. They should overhang 4 rows to the back.

22.3 Vertically place a tan 2x6 brick to the right of the ppps so it overhangs 4 rows to the back and 1 column to the right.

22.4 Place a tan 3x3 wedge plate with cut off corners in front of you so the right angle faces the back left. Now place the back 2 rows of the leftmost column of the plate under the front 2 rows of the right overhang so the right 2 columns of the back row are exposed.

22.5 Horizontally place a tan 1x2 brick on the back row of the ppp. Horizontally place another on the 2 right columns of the 2<sup>nd</sup> row from the front.



22.6 Rotate the sub build 90 degrees counterclockwise. Then Attach it to the right of the main build on the 4 right columns on the 5<sup>th</sup> through 10<sup>th</sup> rows from the front.

23. Horizontally place a dark tan 2x12 plate on the 4<sup>th</sup> and 5<sup>th</sup> rows from the front so it is centered horizontally. Then horizontally place a dark tan 2x4 plate on the 2<sup>nd</sup> 3<sup>rd</sup> 4<sup>th</sup> and 5<sup>th</sup> columns from the left of the 2 front rows. Horizontally place a tan 2x6 plate to the right of the ppp on the 2 front rows since it goes to the right and not to the left of the ppp there is no overhang. Place a dark tan 2x2 plate on the 2<sup>nd</sup> and 3<sup>rd</sup> columns from the right of the 2 front rows.

Building Instructions (Bag 2, Book 1):

Group 7 – Lando Calrissian.

Sub-build 2. Locate a dark brown pair of legs printed with silver and black armor details, a dark brown torso printed with silver and black straps and armor, a medium brown head printed with two faces—one smiling, one serious, a dark brown helmet printed with silver details, a silver spear with a black grip and a guard hook. Assemble the minifigure, then place the helmet on Lando's head. Place the spear on Lando's right hand and clip the guard hook on the top of the spear.

Now he's ready for battle! Set him aside while we continue building the Sarlacc pit.

Group 8: We will place some pieces around the recessed area or pit.

24.1 Horizontally place a nougat 1x2 tile on the 6<sup>th</sup> and 7<sup>th</sup> columns from the left of the third row from the back. Repeat symmetrically to the right.

24.2 Place a nougat 1x2 curved right slope wedge tile vertically to the right of the ppp so the point faces to the front right and 1 row overhangs to the front. To distinguish a right from a left wedge slope curved tile, place the part flat on the table, with the pointed tip facing you and the flat edge at the back. Then feel the angled slope along the sides: If the angled side is on your right, it's a left wedge slope tile. If the angled side is on your left, it's a right wedge slope tile. Place a nougat 1x2 curved left slope wedge tile symmetrically to the left.

25. Rotate the left Technic structure we made before by turning the left lever at the back of the build a quarter turn to the left, so that the pin hole now faces upward and the hole runs back to front. Repeat symmetrically to the right.

26. Vertically place a nougat 1x2 curved right slope wedge tile on the 8<sup>th</sup> column from the left of the 3<sup>rd</sup> row from the back with the point to the front right so it slopes and overhangs 1 row to the front. Place a 1x2 curved left slope wedge tile symmetrically to the right. Place a nougat 1x2 plate with 3 spikes horizontally to the left of the ppp so the spikes point to the front. It should overhang 1 row to the front. Then place another to the left of the ppp.

27. Vertically place a nougat 1x2 tile on the 4<sup>th</sup> column from the left of the 3<sup>rd</sup> and 4<sup>th</sup> rows from the back. Place a nougat 1x2 curved right slope wedge tile horizontally in front of the ppp so it slopes and overhangs 1 column to the right. The point should face the right back. Place a nougat 1x2 plate with 3 spikes vertically in front of the ppp so that the spikes point and overhang 2 columns to the right. Repeat the 3 placements symmetrically to the right.

28. Place a nougat 1x2 curved right slope wedge tile horizontally in front of the ppps so it slopes to the left. It should overhang 1 column to the left. Vertically place a nougat 1x2 tile in front of the right column of the ppp. Repeat both placements symmetrically to the left.

29. Vertically place a nougat 1x2 curved right slope wedge tile on the 6<sup>th</sup> row from the front to the right of the ppp so it slopes to the back, and the point faces the back left. It should overhang

1 row to the back. Place a nougat 1x2 curved right slope wedge tile symmetrically to the right. Place a nougat 1x2 tile horizontally to the left of the ppp. Repeat symmetrically to the left.

30. Horizontally place a nougat 1x2 plate with 3 spikes to the right of the ppp so the spikes face the back. 2 rows should overhang to the back. Repeat symmetrically to the right. Place a nougat 1x2 curved right slope wedge tile vertically to the left of the ppp so it slopes to the back. The point should face the back left and 1 row overhangs to the back. Place a nougat 1x2 curved left slope wedge tile symmetrically to the left.

Group 9:

31.1 Let's make a part! Vertically place a black 1x8 plate in front of you. Horizontally place the right column of a black 2x3 brick on the 2 back rows of the ppp so 2 columns overhang to the left.

31.2 Vertically place the 2 back rows of a tan 1x6 plate underneath the leftmost overhanging column of the ppp.

31.3 Vertically place a black 1x4 brick on the 4 front rows of the ppp. Keeping the same position place this on the 3 leftmost columns of the 3<sup>rd</sup> row from the back so that the 1x8 plate is to the left of the 1x2 sloped curved tiles and the plates with spikes.

32.1 Let's make a part! Vertically place a tan 1x6 plate in front of you. Horizontally place the right column of a black 2x3 brick on the 2 back rows of the ppp so 2 columns overhang to the left.

32.2 Vertically place the 2 back rows of a black 1x8 plate underneath the leftmost column of the ppp.

32.3 Vertically place a black 1x4 brick on the 4 front rows of the tan 1x6 plate. Vertically place this on the 3 rightmost columns of the 3<sup>rd</sup> row from the back so that the 1x8 plate is to the right of the 1x2 sloped curved tiles and the plates with spikes.

33.1 Let's make a part! Horizontally place a gray 1x4 brick with 4 side studs on the long side in front of you so the side studs face the front.

33.2 Place a white fang on the rightmost front facing side stud so it curves downward. Then place a dark red 1x1 round plate with open stud on the leftmost front facing side stud.

33.3 Place a white fang on the ppp so it curves downward. Place another on the 3<sup>rd</sup> front facing side stud from the left so it curves downward. Rotate the sub build 90 degrees clockwise so the fangs point to the left. Vertically place the sub build on the 5<sup>th</sup> through 8<sup>th</sup> rows from the back on the 7<sup>th</sup> column from the right counting the entire build, which is on top of the right 1x8 plate.

34.1 Let's make a part! Horizontally place a gray 1x4 brick with 4 side studs on the long side in front of you so the side studs face the front. Place 3 white fangs on the 3 right front facing side studs so they curve downward.

34.2 Place a dark red 1x1 slope tile on the leftmost front facing side stud so it slopes up. Rotate the sub build 90 degrees counterclockwise so the fangs face the right. Vertically place the sub build on the 5<sup>th</sup> through 8<sup>th</sup> rows from the back on the 7<sup>th</sup> column from the left counting the entire build, which is on top of the left 1x8 plate.

35. Vertically place a tan 1x6 brick on the 4<sup>th</sup> through 9<sup>th</sup> rows from the back on the 4<sup>th</sup> column from the right counting the entire build. Repeat symmetrically to the left.

Group 10:

36.1 Vertically place a dark tan 1x2 log brick on the 6<sup>th</sup> and 7<sup>th</sup> rows from the front and on the 7<sup>th</sup> column from the left counting the entire build, in front of the 1x4 brick with fangs. Repeat symmetrically to the right.

36.2 Horizontally place the left column of a gray 1x2 log brick in front of the ppp. Repeat symmetrically to the left.

36.3 Vertically place a gray 1x2 log brick to the left of the ppp on the 6<sup>th</sup> and 7<sup>th</sup> rows from the front on the 5<sup>th</sup> column from the left. Repeat symmetrically to the right.

37. Horizontally place a dark red 1x2 rounded plate on the 5<sup>th</sup> row from the front on the 6<sup>th</sup> and 7<sup>th</sup> columns from the right counting the entire build, to the left of the ppp. Repeat symmetrically to the left.

38.1 Let's make a part! Horizontally place a gray 1x4 brick with 4 side studs on the long side in front of you so the side studs face the front. Place a white fang on the rightmost front facing side stud so it curves downward.

38.2 Place a dark red 1x1 round plate with open stud on the front facing stud to the left of the ppp.

38.3 Horizontally place a gray 1x4 brick with 4 side studs on the long side to the left of the sub build with the side studs facing the front. Then Place the left column of a dark red 1x2 rounded plate on the rightmost front facing side stud of the ppp, and the right column on the leftmost front facing side stud of the sub build.

38.4 Place a dark red 1x1 round plate with open stud to the left of the ppp. Then place a dark red 1x1 slope tile to the left of the ppp so it slopes down.

38.5 Place a white fang on the leftmost front facing side stud so it curves downward. Place 4 more on the 3<sup>rd</sup>, 4<sup>th</sup>, 6<sup>th</sup>, and 7<sup>th</sup> front facing side studs from the left so they curve downward. Place the sub build horizontally on the 8 right columns of the back row so the white fangs face the front.

39.1 Let's make a part! Horizontally place a gray 1x4 brick with 4 side studs on the long side in front of you so the side studs face the front. Place a white fang on the leftmost front facing side stud so it curves downward.

39.2 Horizontally place a dark red 1x2 rounded plate to the right of the ppp. Then place a dark red 1x1 slope tile to the right of the ppp so it slopes downward.

39.3 Place 2 white fangs on the 2<sup>nd</sup> and 3<sup>rd</sup> front facing side studs from the right so they curve downward. Horizontally place the sub build on the 4 left columns of the back row, to the left of the previous attached sub build. The white fangs should face the front.

40.1 Let's make a part! Horizontally place a gray 1x4 brick with 4 side studs on the long side in front of you so the side studs face the front. Place a dark red 1x1 slope tile on the rightmost front facing side stud so it slopes down.

40.2 Place a dark red 1x2 rounded plate horizontally upright to the left of the ppp. Then place another to the left of the ppp so it overhangs 1 column to the left.

40.3 Horizontally attach the rightmost front facing side stud of a gray 1x4 brick with 4 side studs on the long side to the left antistud column of the ppp.

40.4 Horizontally place a dark red 1x2 rounded plate on the 2<sup>nd</sup> and 3<sup>rd</sup> front facing side studs from the left. Place a dark red 1x1 round plate on the 2<sup>nd</sup> and 4<sup>th</sup> front facing side studs from the right.

40.5 Place a white fang on the 2<sup>nd</sup>, 4<sup>th</sup>, 5<sup>th</sup>, and 7<sup>th</sup> front facing side studs from the left. They should all curve downward. Rotate the sub build 180 degrees so the fangs face the back, then place it on the 4<sup>th</sup> row from the front on the 9<sup>th</sup> through 16<sup>th</sup> columns from the right, so it sits on the 8 right columns of the front row of the tan 2x12 plate.

41.1 Let's make a part! Horizontally place a gray 1x4 brick with 4 side studs on the long side in front of you so the side studs face the front. Place a dark red 1x2 rounded plate on the 2 right front facing side studs.

41.2 Place a white fang on the 3 left front facing side studs. They should all curve downward. Rotate it 180 degrees so the fangs face the back. Place it horizontally on the 4<sup>th</sup> row from the front on the 9<sup>th</sup> through 12<sup>th</sup> columns from the left.

42. Horizontally place a black 1x4x2 wall panel on the 3<sup>rd</sup> row from the front so it is centered horizontally, and the wall faces the front.

Building Instructions (Bag 3, Book 1):

#### Group 11 - Luke Skywalker

Sub-build 3. Locate a pair of black legs printed with subtle fabric details, a dark gray torso printed with folds and a belt, and a tan head printed with two faces—one calm, one determined, a dark tan hairpiece, a green lightsaber, and a silver hilt. Assemble the minifigure. Then assemble the silver hilt at the bottom of the lightsaber and place it in Luke's right hand. Now he's ready for battle! Set him aside while we continue building the Sarlacc pit.

#### Group 12:

43. Place 2 black 2x2 inverted slope bricks, one to the left of the other, on the 4 leftmost columns of the 2<sup>nd</sup> row from the back so they slope and overhang 1 row to the back, and so they align with the back of the build. Repeat symmetrically to the left.

44. Horizontally place a tan 2x4 plate on the ppps. Repeat symmetrically to the right.

45. Vertically place a tan 1x2 brick on the 2 back rows of the 4<sup>th</sup> column from the left.

46. Place a tan 1x2x2 brick on the 2<sup>nd</sup> and 3<sup>rd</sup> rows from the back of the 3<sup>rd</sup> column from the left. Vertically place the right column of a tan 2x4 slope brick in front of the ppp, on the 2<sup>nd</sup> and 3<sup>rd</sup> columns from the left of the 5<sup>th</sup> through 8<sup>th</sup> rows from the front, so it slopes to the left.

47. Horizontally place the left column of a tan 3x2 slope brick on the 2 front rows of the ppp so it slopes to the left. Then place a tan 2x2 slope brick behind the 2 left columns of the ppp so it slopes to the left.

48. Horizontally place a white 2x3 brick on the 2 leftmost columns of the 3<sup>rd</sup> and 4<sup>th</sup> rows from the front so the left column overhangs to the left.

49. Orient a dark tan 6x3 left wedge plate with cut corner in front of you so the cut corner points to the back left. In this position attach the back right corner under the front row of the left overhanging column of the ppp. 5 columns are exposed to the left, and 2 rows to the front. The 2 rows align with the 2 front rows of the build.

50. Place a tan 2x2 corner brick in front of you so it looks like a braille letter H. place it on the 2<sup>nd</sup> and 3<sup>rd</sup> rows from the front and on the 5<sup>th</sup> and 6<sup>th</sup> columns from the left, so it sits around the front left corner of the white 2x3 brick. Vertically place a dark tan 1x2 slope brick on the 2 front rows on the 7<sup>th</sup> column from the left counting the entire build, so it slopes to the front.

51. Vertically place a tan 1x3 slope brick on the 3 front rows of the 4<sup>th</sup> column from the left, so it slopes to the front. Horizontally place a dark tan 1x2 slope brick on the 2<sup>nd</sup> row from the front of

the 2<sup>nd</sup> and 3<sup>rd</sup> columns from the left so it slopes to the left. Then place a dark tan 1x1 slope tile on the front row of the 3<sup>rd</sup> column from the left, in front of the right column of the ppp. It should slope to the front.

52.1 Place a tan 2x2x2 slope brick on the 2<sup>nd</sup> and 3<sup>rd</sup> rows from the front on the 6<sup>th</sup> and 7<sup>th</sup> columns from the left, so it slopes to the front.

52.2 Then place a dark tan 1x2 slope brick to the left of the ppp so it slopes to the front. Now horizontally place a dark tan 1x2 slope brick on the 2<sup>nd</sup> row from the front of the 3<sup>rd</sup> and 4<sup>th</sup> columns from the left.

53. Place a tan 2x2 corner plate on the ppp so it looks like the braille letter D.

#### Group 13:

54. Rotate the build 90 degrees clockwise so the 1x2 liftarms with axle hole and pin hole are on the right. Horizontally place a tan 1x2 brick on the 2 right columns of the 4<sup>th</sup> row from the front.

55. Place a tan 2x2x2 slope brick on the 2<sup>nd</sup> and 3<sup>rd</sup> columns from the right of the 2<sup>nd</sup> and 3<sup>rd</sup> rows from the front, so it slopes to the front. Horizontally place a tan 2x4 slope brick to the left of the ppp, so it slopes to the front. The front row sits on the back row of a previously placed 2x4 slope brick.

56. Place the front row of a tan 2x2 slope brick to the left of the back row of the tan 2x2x2 slope brick from the previous step, so it slopes to the front. Vertically place the 2 front columns of a tan 2x3 slope brick to the left of the ppp so it slopes to the front.

57. Vertically place a white 2x3 brick on the 6<sup>th</sup> 7<sup>th</sup> and 8<sup>th</sup> rows from the front on the 3<sup>rd</sup> and 4<sup>th</sup> columns from the left, the right column of the back row sits in front of the front 1x4 brick with fangs and 1 row overhangs to the front.

58. Orient a dark tan 6x3 right wedge plate with cut corner in front of you so the cut corner points to the front right. In this position attach the back right corner under the left column of the front row of the ppp. 2 columns are exposed to the left and 5 rows to the front. The 2 left columns align with the 2 left columns of the build.

59. Place a tan 2x2 corner brick on the 5<sup>th</sup> and 6<sup>th</sup> rows from the front on the 2<sup>nd</sup> and 3<sup>rd</sup> columns from the left so it looks like a braille letter H. Then horizontally place a dark tan 1x2 slope brick on the 7<sup>th</sup> row from the front on the 2 left columns so it slopes to the left.

60. Horizontally place a tan 1x3 slope brick on the 3 left columns of the 4<sup>th</sup> row from the front so it slopes to the left. Then place a dark tan 1x2 slope brick vertically on the 2<sup>nd</sup> column of the 2<sup>nd</sup> and 3<sup>rd</sup> rows from the front so it slopes to the front. Place a dark tan 1x1 slope tile on the leftmost column of the 3<sup>rd</sup> row from the front so it slopes to the left.

61. Vertically place a dark tan 1x2 slope brick on the 3<sup>rd</sup> and 4<sup>th</sup> rows from the front on the 4<sup>th</sup> column from the left counting the entire build, so it slopes to the front. The front row goes on the dark tan 1x2 slope brick you placed in the previous step. Horizontally place a dark tan 1x2 slope brick on the left 2 columns of the 5<sup>th</sup> row from the front, so it slopes to the left. Place a tan 2x2x2 slope brick behind the ppp so it slopes to the left.

62. Place a tan 2x2 corner plate on top of the 2 1x2 slope bricks from the previous step so it looks like a braille letter D.

#### Group 14:

63.1 Rotate the build 90 degrees counter clockwise so the levers are in the back. Place a tan 2x2x2 slope brick on the 2 front rows on the 8<sup>th</sup> and 9<sup>th</sup> columns from the left so it slopes to the

front. Repeat symmetrically to the right. Place another to the left of the ppp so it slopes to the front.

63.2 Then place a tan 2x2 slope brick to the left of the ppp so it slopes to the front. Then place a tan 2x2x2 slope brick to the left of the ppp so it slopes to the front.

63.3 Horizontally place a tan 1x2x2 brick on the 2<sup>nd</sup> row from the front to the left of the ppps. Place a tan 2x2 slope brick to the left of the ppp on the 2 front rows so it slopes to the front. Horizontally place a blue 1x6 plate on the 3<sup>rd</sup> row from the front so it is centered horizontally, it sits on the black 1x4x2 wall panel.

64. Place a dark tan 1x1 slope tile on the front row on the 13<sup>th</sup> column from the left counting the entire build so it slopes to the front. Place a tan 1x2 brick horizontally on the 2<sup>nd</sup> row from the front on the 10<sup>th</sup> and 11<sup>th</sup> columns from the left. Place another horizontally on the 2<sup>nd</sup> row from the front on the 12<sup>th</sup> and 13<sup>th</sup> columns from the right. Then place a tan 1x2 slope tile horizontally to the right of the ppp, on the 10<sup>th</sup> and 11<sup>th</sup> columns from the right, so it slopes to the front.

Group 15:

65.1 Let's make a part! Horizontally place a dark tan 2x12 plate in front of you. Vertically place a tan 1x2 curved right slope wedge tile on the front row on the 2<sup>nd</sup> column from the left so 1 row overhangs to the front and the point faces to the front right. Place a tan 1x2 curved left slope wedge tile symmetrically to the right.

65.2 Place a tan 2x2 curved slope tile on the front row, to the left of the ppp so it slopes and overhangs 1 row to the front. Repeat symmetrically to the left.

65.3 Vertically place a tan 1x2 curved left slope wedge tile to the right of the ppp so it slopes to the front and 1 row overhangs to the front. Vertically place a tan 1x2 curved right slope wedge tile to the right of the ppp. Repeat both placements symmetrically to the right.

65.4 Rotate the sub build 180 degrees so the slopes slope to the back. Place it on the 3<sup>rd</sup> and 4<sup>th</sup> rows from the front so it is centered horizontally.

66. Place a tan 2x2 curved slope tile on the 2<sup>nd</sup> and 3<sup>rd</sup> rows from the front on the 8<sup>th</sup> and 9<sup>th</sup> columns from the left so it slopes to the front. Place 4 more to the right of the ppp so they slope to the front. Then place another on the 2<sup>nd</sup> and 3<sup>rd</sup> rows from the front on the 8<sup>th</sup> and 9<sup>th</sup> columns from the right so it slopes to the front.

Building Instructions (Bag 4, Book 1):

Group 16 - Han Solo.

Sub build4. Locate a pair of brown legs printed with a belt, a tan torso printed with a white shirt, a tan head printed with a determined expression, a brown hairpiece, and a gray pair of handcuffs.

Assemble the minifigure. Place Han's hands inside each side of the pair of handcuffs. Han Solo is ready for action! Set him aside while we finish building the Sarlacc pit.

Group 17:

67. Horizontally place a dark tan 1x4 plate on the 4<sup>th</sup> through 7<sup>th</sup> columns from the left of the back row. Then place a tan 1x3 plate horizontally to the right of the ppp. Place another symmetrically to the right of the ppp. Place a dark tan 1x4 plate horizontally to the right of the ppps.

68.1 Let's make a part! Vertically place a dark tan 2x12 plate in front of you. Vertically place a light blue 2x3 plate on the 2<sup>nd</sup> 3<sup>rd</sup> and 4<sup>th</sup> rows from the back. Repeat symmetrically to the front.

68.2 Horizontally place the right column of a black 1x2 plate on the 5<sup>th</sup> row from the back on the leftmost column, so 1 column overhangs to the left. Horizontally place the right column of a dark tan 1x2 plate on the front row on the leftmost column, so 1 column overhangs to the left.

68.3 Vertically place a tan 1x8 plate under the left overhang so its front and back rows attach to the anti studs.

68.4 Place a tan 2x2 corner plate on the 4<sup>th</sup> and 5<sup>th</sup> rows from the front on the 2 leftmost columns so it looks like the braille letter F. Rotate the sub build 180 degrees. Vertically attach it so the back row of your part sits on the 3 rightmost columns of the back row of the main build and there is no overhang.

69. Horizontally place a tan 1x3 tile on the 3<sup>rd</sup>, 4<sup>th</sup>, and 5<sup>th</sup> columns from the right of the back row. Vertically place a tan 1x2 curved left wedge slope tile to the left of the ppp, so it slopes to the front and 1 row overhangs to the front. Then place a tan 2x2 curved slope tile to the left of the ppp, so it slopes to the front and 1 row overhangs to the front. Vertically place a tan 1x2 curved right slope wedge tile to the left of the ppp, so it slopes to the front and 1 row overhangs to the front.

70. Vertically place a tan 1x2 curved left slope tile on the 10<sup>th</sup> column from the right of the back row to the left of the ppp, so it slopes to the front and 1 row overhangs to the front. Then place a tan 2x2 curved slope tile to the left of the ppp, so it slopes to the front and 1 row overhangs to the front. Vertically place a tan 1x2 curved right slope wedge tile to the left of the ppp, so it slopes to the front and 1 row overhangs to the front. Vertically place a tan 1x2 curved left slope wedge tile to the left of the ppp so it slopes to the front and 1 row overhangs to the front. Then place a tan 1x2 curved right slope wedge tile to the left of the ppp so it slopes to the front and 1 row overhangs to the front. The 5 left columns of the back row should be empty.

Group 18:

71.1 Let's make a part! Vertically place a dark tan 2x12 plate in front of you. Vertically place a light blue 2x3 plate on the 2<sup>nd</sup> 3<sup>rd</sup> and 4<sup>th</sup> rows from the back. Repeat symmetrically to the front.

71.2 Horizontally place the left column of a black 1x2 plate on the 5<sup>th</sup> row from the back on the rightmost column, so 1 column overhangs to the right. Horizontally place the left column of a dark tan 1x2 plate on the front row on the rightmost column, so 1 column overhangs to the right.

71.3 Vertically place a tan 1x8 plate under the right overhang. The front and back rows should attach to the anti studs.

71.4 Place a green 2x2 corner plate so it looks like a braille letter D on the 4<sup>th</sup> and 5<sup>th</sup> rows from the front on the 2 right columns. Rotate the sub build 180 degrees. Attach it vertically so the back row attaches to the 3 left columns of the back row.

72. Horizontally place a tan 1x3 tile on the 3<sup>rd</sup>, 4<sup>th</sup>, and 5<sup>th</sup> columns of the back row of the main build. Then horizontally place a dark tan 1x4 plate on the 4<sup>th</sup> row from the front on the 6<sup>th</sup> through 9<sup>th</sup> columns from the left. The left 2 columns go on the front row of the attached sub build from the previous step. Repeat symmetrically to the right.

73.1 Place a dark tan 2x2 plate on the 3<sup>rd</sup> and 4<sup>th</sup> columns from the left of the 4<sup>th</sup> and 5<sup>th</sup> rows from the back. Repeat symmetrically to the right.

73.2 Place a dark tan 2x2 plate on the 2<sup>nd</sup> and 3<sup>rd</sup> columns of studs from the right of the 5<sup>th</sup> and 6<sup>th</sup> rows of studs from the front. Place another on the 3<sup>rd</sup> and 4<sup>th</sup> columns of studs from the left of the 5<sup>th</sup> and 6<sup>th</sup> rows of studs from the front.

73.3 Place a dark tan 2x2 plate on the 3<sup>rd</sup> and 4<sup>th</sup> columns of studs from the left of the 3<sup>rd</sup> and 4<sup>th</sup> rows of studs from the front. Place another on the 2<sup>nd</sup> and 3<sup>rd</sup> columns from the right of the 3<sup>rd</sup> and 4<sup>th</sup> rows from the front counting the free studs.

74. Place a tan 2x2 curved slope tile on the 2 left columns of the 2<sup>nd</sup> and 3<sup>rd</sup> rows from the back, so it slopes to the left. Place another on the 4<sup>th</sup> and 5<sup>th</sup> rows from the back on the 4<sup>th</sup> and 5<sup>th</sup> columns from the left counting the entire build. It should slope to the left. Place another on the 7<sup>th</sup> and 8<sup>th</sup> rows from the front on the 4<sup>th</sup> and 5<sup>th</sup> columns from the left, so it slopes to the left. Place another on the 5<sup>th</sup> and 6<sup>th</sup> rows from the front on the 5<sup>th</sup> and 6<sup>th</sup> columns from the left. Repeat the 4 placements symmetrically to the right.

75. Place a tan 2x2 curved left slope wedge tile on the 3<sup>rd</sup> and 4<sup>th</sup> columns from the right of the 2<sup>nd</sup> and 3<sup>rd</sup> rows from the back, so it slopes to the left. The point should face the left back. Place another horizontally in front of the ppp so it slopes to the left. The point should face the left back. It overhangs 1 column to the left. Repeat both placements using tan 2x2 curved right slope wedge tiles to the left.

76.1 Let's make 2 identical parts! Place a dark tan 2x2 plate in front of you. Then vertically place a nougat 1x2 plate on the right column of the ppp. Horizontally place a tan 3x2 curved slope tile on the left column of the 2x2 plate so it slopes to the left. 2 columns should OVERHANG to the left. Then place a tan 2x2 curved slope tile on the rightmost column so it slopes to the right. You should now have 2 identical parts.

76.2 Place the first part horizontally on the 6<sup>th</sup> and 7<sup>th</sup> rows from the back and on the 3<sup>rd</sup> through 7<sup>th</sup> columns from the right. The tan 3x2 curved slope tile should slope to the left. Place the 2<sup>nd</sup> part symmetrically to the left.

77. Horizontally place a tan 2x3 curved left slope wedge tile on the 5<sup>th</sup> and 6<sup>th</sup> rows from the front and on the 7<sup>th</sup> column from the left counting the entire build, so it slopes to the right. 2 columns should overhang to the right. Place another on the 7<sup>th</sup> and 8<sup>th</sup> rows from the front on the 6<sup>th</sup> and 7<sup>th</sup> columns from the left counting the entire build, so it slopes to the right. 1 column should overhang to the right. Repeat both placements symmetrically to the right using tan 2x3 curved right slope wedge tiles.

78. Horizontally place a tan 2x3 curved left slope wedge tile on the 3<sup>rd</sup> and 4<sup>th</sup> rows from the front on the 4<sup>th</sup> through 6<sup>th</sup> columns from the left counting the entire build, so it slopes to the left. The point should face the left back. Place a dark tan 1x1 slope tile on the 4<sup>th</sup> row from the front on the 7<sup>th</sup> column from the left, so it slopes to the front counting the entire build. Repeat both placements symmetrically to the right, using a tan 2x3 curved right slope wedge tile.

Group 19:

79. Let's make 2 identical parts! Let's build the tentacles! Attach a brown tail tip to a brown tail section following the same curving direction. Now you should have 2 identical parts!

80. Insert the bottom pin of the first part into the back left top facing pin hole, so the end points to the back left. Then insert the bottom pin of the second part into the front right top facing pinhole so the end points to the right.

81. Let's make 2 identical parts! Horizontally place a brown tail section in front of you so it curves to the back. Insert the pin of a brown tail section which has the shape of an elephant trunk to the right facing hole of the ppp following the same curving direction. You should now have 2 identical parts!

82. Insert the bottom pin of the first part into the back right top facing pin hole so it stands upright and the end points to the back right. Insert the bottom pin of the second part into the front left top facing pinhole so it stands upright and the end points to the left.



83. Let's build the mouth of the monster Sarlacc pit! Vertically attach the bar handle of a dark tan 6x4x2 windscreen with bar handle to the left column of upright clips located in the center of the build. The hollow side should face the right. Repeat symmetrically to the right. You can keep the mouth of the Sarlacc open, or you can close it. The Sarlacc Pit's build is complete!

Building Instructions (Bag 5, Book 2):

Group 20 - Chewbacca.

Sub build 5. Locate a pair of medium nougat-colored legs printed with fur texture, a plain brown torso, and a single molded head & upper body piece showing Chewbacca's facial details, fur texture, and bandolier. Assemble the minifigure, then attach the head & upper body piece over the torso. Chewbacca is ready for action! Set him aside while we start building the desert Skiff.

Desert Skiff

Group 21:

1. Horizontally place a grey 6x6 triple inverted wedge plate in front of you with the short side facing to the right. Vertically place a gray 1x2 plate with a rail on the rightmost column so it is centered vertically.

2. Vertically place another gray 1x2 plate with a rail on top of the ppp so the rail is on the right.

Then horizontally place a gray 2x8 plate to the left of the ppp so 3 columns overhang to the left.

3. Vertically place a 4x6 plate with inverted sloped sides under the 3 left overhanging columns so it is aligned with the right side of the build.

4. Vertically place a gray 2x6 plate on the rightmost column so it is centered vertically and 1 column overhangs to the right. Vertically place a dark tan 1x6 tile on the right column of the ppp. Vertically place a dark grey 1x2 ingot tile on the 2<sup>nd</sup> and 3<sup>rd</sup> rows from the front on the 2<sup>nd</sup> column from the right. Repeat symmetrically to the back.

5.1 Let's make a part! Place a blue 2x2 plate in front of you. Vertically place a pink 1x2 plate on the right column of the ppp.

5.2 Vertically place a gray 1x6 plate on the left column so it is centered vertically.

5.3 Vertically place a tan 2x4 plate on the ppps so it is centered vertically. the right column overhangs 1 row to the front and back.

5.4 Vertically place the back row of a gray 1x2 plate with 2 hinge fingers on the short side underneath the front overhang of the ppp so one row and the hinge fingers are exposed to the front. Repeat symmetrically to the right.

5.5 Vertically place your part on the 3<sup>rd</sup> and 4<sup>th</sup> columns from the right counting the entire build so it is centered vertically, and the hinges are on the right and face the front and back. Repeat symmetrically to the back.

6.1 Let's make a part! Horizontally place a tan 2x4 plate in front of you.

6.2 Horizontally place a gray 2x6 plate on the front row of the ppp so it is centered horizontally and 1 row overhangs to the front.

6.3 Place the studs of 3 gray 2x2 tiles with 2 studs, one to the right of the other, underneath the front row so the tile is exposed to the front.

6.4 Turn the sub build upside down so the 2x2 tiles face the front. Horizontally place a grey 1x2 inverted curved slope tile on the 2<sup>nd</sup> row of antistuds from the back on the 2 left columns, so it

slopes to the left. Repeat symmetrically to the right. Orient a gray 2x2 corner plate so it looks like the braille letter h. then place the back row to the left of the ppp. Repeat symmetrically to the left. Now vertically place a gray 1x2 plate on the second column from the right so it overhangs 1 row to the front.

6.5 Flip the sub build right side up, so the tiles are in the front and the ppp is exposed 1 row to the front.

Then rotate your part 90 degrees clockwise so the ppp is now exposed 1 column to the left.

Vertically place the right column of the sub build on the leftmost column of the main build so it is centered vertically.

7. Vertically place a tan 2x4 plate on the 5<sup>th</sup> and 6<sup>th</sup> columns from the left so it is centered vertically. Vertically place a dark grey 1x2 ingot tile to the right of the ppp so it is centered vertically. Horizontally place a grey 1x4 tile with 2 studs to the right of the back row of the ppp on the 3<sup>rd</sup> row from the back. Repeat symmetrically to the front.

Group 22:

8.1 Let's make a part! Horizontally place a grey 6x6 triple inverted wedge plate in front of you, so the short side faces the left.

8.2 Vertically place an orange 2x4 plate on the ppp so it is centered horizontally and vertically. Then place a dark tan 2x2 plate to the right of the front 2 rows of the ppp.

8.3 Horizontally place a grey 1x3 tile on the 2<sup>nd</sup> row from the back on the 2 right columns so 1 column overhangs to the right.

8.4 Vertically place an orange 2x4 plate on the 2 right columns so it is centered vertically. Horizontally place a blue 1x2 plate to the left of the front row of the ppp. Repeat symmetrically to the back.

8.5 Let's make a part which we will then attach to the main sub build! Place a grey 4x4 triple inverted wedge plate in front of you so the short end points to the left. vertically place an orange 1x2 plate on the rightmost column so it is centered vertically. Then horizontally place the 2 left columns of a black 2x6 plate on the 2 rightmost columns o it is centered vertically, and 4 columns overhang to the right.

Place the right overhang of your part on the 4 leftmost columns of the previous sub build so it is centered vertically.

8.6 Attach the sub build to the main build by attaching the right overhang to the left facing 1x2 plate on the second row from the back. It will only attach by one stud.

9. Horizontally place a grey 6x12 plate on the 5<sup>th</sup> through 16<sup>th</sup> columns from the right counting the entire build. Vertically place a grey 1x6 plate to the left of the ppp.

10. Horizontally place a grey 3x4 wedge plate with cutout on the 2<sup>nd</sup>, 3<sup>rd</sup>, and 4<sup>th</sup> columns from the left. Vertically place a dark tan 1x2 tile on the leftmost column. Place a dark tan 2x2 plate on the 4<sup>th</sup> and 5<sup>th</sup> columns from the left so it is centered vertically. Horizontally place a dark tan 2x3 plate to the right of the ppp.

11. Place a grey 2x2 tile with 2 studs on the 2 back rows on the 5<sup>th</sup> and 6<sup>th</sup> columns from the left so the 2 studs point horizontally to the front. Repeat symmetrically to the front.

12. Horizontally place a dark tan 1x6 tile on the front row on the 2<sup>nd</sup> through 7<sup>th</sup> columns from the right counting the entire build. Repeat symmetrically to the back. Vertically place a grey 1x4 plate on the 5<sup>th</sup> column from the right so it is centered vertically.

13. Let's make a part! Let's build the push-out plank! Vertically place a grey 2x6 tile in front of you. Then place a black 1x1 short brick with a round side and a side stud under the left column of the front row so the side stud faces the front. Then place a dark tan 1x1 round tile on the front facing side stud. Now insert the back of the sub-build keeping this same position, sliding it into the horizontal slot at the front between columns 11 and 12 from the left counting the entire build. The platform slides backward until the 1x1 short brick with a rounded side and side stud acts as a stopper.

14. Horizontally place a dark tan 1x6 tile on the back row on the 8<sup>th</sup> through 13<sup>th</sup> columns from the right counting the entire build. Then horizontally place a dark tan 1x2 tile to the left of the ppp. Horizontally place a dark tan 1x6 plate on the front row on the 8<sup>th</sup> through 13<sup>th</sup> columns from the right. Horizontally place a dark tan 1x2 plate with 1x2 side studs hanging down to the left of the ppp so the side studs face the front.

15. Stack 2 grey 2x4 plates and place the stacked pieces vertically on the 6<sup>th</sup> and 7<sup>th</sup> columns from the right counting the entire build, so they are centered vertically.

16.1 Vertically place a nougat 1x4 tile to the left of the ppps so it is centered vertically. Then place a nougat 1x4 tile with 2 studs horizontally to the left of the front row of the ppp. Repeat symmetrically to the back.

16.2 Place a grey 2x2 tile with stud on the 9<sup>th</sup> and 10<sup>th</sup> columns from the right counting the entire build, so it is centered vertically. Place another to the left of the ppp.

17. Horizontally place a dark tan 1x3 plate on the ppps. Then place a dark tan 1x3 tile horizontally on the ppp.

18. Vertically place a nougat 2x4 plate on the 12<sup>th</sup> and 13<sup>th</sup> columns from the left counting the entire build, so it is centered vertically. Place a nougat 1x1 tile on the 2<sup>nd</sup> row from the front on the 11<sup>th</sup> column from the left. Repeat symmetrically to the back. Place a nougat 2x2 tile with 2 studs to the left of the ppp on the 2 back rows with the studs pointing vertically to the left. Repeat symmetrically to the front.

#### Group 23:

19.1 Place a nougat 1x1 slope tile on the 2<sup>nd</sup> row from the front on the 9<sup>th</sup> column from the right counting the entire build, so it slopes to the back. Repeat symmetrically to the back.

19.2 Then place a dark tan 1x1 slope tile on the front row on the 9<sup>th</sup> column from the left counting the entire build, which is covered, so it slopes to the right. Repeat symmetrically to the back.

20. Horizontally place a nougat 2x6 tile on the 6<sup>th</sup> through 11<sup>th</sup> columns from the left so it is centered vertically. Horizontally place a black 1x2 plate with stud and upright clip on the front row of studs of the 3<sup>rd</sup> and 4<sup>th</sup> columns from the left counting the entire build, so the clip faces the left and the hands of the clip face left to right. Repeat symmetrically to the back.

21. Place a nougat 2x2 curved slope tile on the right column of the ppps so it slopes to the right.

22.1 Let's make a part! Horizontally place a dark tan 2x4 plate in front of you. Vertically place a dark tan 1x2 triple slope brick on the rightmost column, so it slopes to the right front and back.

22.2 Place a dark tan 2x2 double slope brick to the left of the ppp so it slopes to the front and back. Place a dark tan 2 x 1 double slope brick with bottom stud holder to the left of the ppp so the tip points to the left.

22.3 Let's make a part! Place a grey 2x2 plate in front of you. Then place a grey 2x2 plate with horizontal bar on bottom underneath the ppp so the horizontal bar is oriented vertically underneath the right column. In this position place the part under the main sub build so it is centered horizontally. Attach the vertical bar on the bottom of the sub build to the upright clips on the left of the main build.

Group 24:

23.1 Let's make a part! Horizontally place a dark tan 2x3 plate in front of you. Vertically place a grey 1x2 plate with 2 clips on the long side on the rightmost column so the clips face the right.

23.2 Vertically place a dark tan 1x2 plate to the left of the ppp. Then vertically place the 1x2 plate of a grey 2x2 tile with upright 1x2 plate to the left of the ppp so the side antistuds face the left.

23.3 Vertically place the back 2 rows of a dark tan 8x3x2 left wedge shell on the 2 left columns of the sub build so the wedge point faces the front left. Flip it so it sits on its left facing side then rotate it 90 degrees clockwise and place the 2x2 antistuds of the 2x2 tile with upright 1x2 plate vertically on the 2 back rows of the 3<sup>rd</sup> and 4<sup>th</sup> columns of studs from the left. The wedge's point should face the left. It sits on a horizontal blue 1x2 plate.

24.1 Let's make a part! Horizontally place a dark tan 2x3 plate in front of you. Vertically place a grey 1x2 plate with 2 clips on the long side on the rightmost column so the clips face the right.

24.2 Vertically place a dark tan 1x2 plate to the left of the ppp. Then vertically place a grey 1x2 plate of a 2x2 tile with upright 1x2 plate to the left of the ppp so the side antistuds face the left.

24.3 Vertically place the front 2 rows of a dark tan 8x3x2 right wedge shell on the 2 left columns of the sub build so the point faces the back left. Flip it so it sits on its left facing side then rotate it 90 degrees counterclockwise and place the 2x2 antistuds of the dark grey 2x2 tile with upright 1x2 plate on the 2 front rows of the 3<sup>rd</sup> and 4<sup>th</sup> columns of studs from the left. The wedge's point should face the left. It should be symmetrical to the previous build. It sits on a horizontal blue 1x2 plate.

25. Insert one end of a nougat-colored 12L hose into the upward-facing clips in the front row. Curve the hose to the left, then connect the other end to the upward-facing clips in the back row. Both ends should point to the right, with the hose forming a smooth arc to the left.

Building Instructions (Bag 6, Book 2):

Group 25 - Nien Nunb

Sub build 6. Locate a pair of dark red legs printed with flight suit details, a dark red torso printed with a black pilot's vest, and a single molded head & helmet piece showing a tan face with printed brown eyes and a brown flying helmet.

1. Assemble the minifigure.

2. The Nien Nunb 25th Anniversary minifigure is placed on a commemorative display stand which has a printed anniversary tile. Let's build it! Horizontally place a black 4x6 tile with studs on edges with a printed special design in front of you so the side with no studs faces the front. In the printing appears The LEGO Star Wars 25th Anniversary logo, which is the droid R2D2, and the words 25 Years of Lego "Star Wars" in silver. Horizontally place a black 1x6 arch brick under the back row of the ppp. Repeat symmetrically to the front.

3. Place Nien Nunb centered horizontally on the back row so that he is standing up and looking to the front. Set him aside while we finish building the Desert Skiff.

Group 26:

26. Rotate the Desert Skiff 180 degrees. Horizontally place a grey 1x2 jumper plate on the 3<sup>rd</sup> row from the back on the 4<sup>th</sup> and 5<sup>th</sup> columns from the left counting the entire build. Repeat symmetrically to the front. Stack 2 grey 1x2 plates with rail then place the stack vertically to the left of the pppps so the rail points to the left.

27. Horizontally place a grey 1x2 plate with 2x2 upright side studs on the 2<sup>nd</sup> row from the front (the 1<sup>st</sup> is covered) on the 3<sup>rd</sup> and 4<sup>th</sup> columns from the left counting the entire build, so the side studs face the front. Repeat symmetrically to the back. Place a grey 1x1 plate with upright 1x2 side studs to the right of the ppp, so the side studs face the back. Repeat symmetrically to the front.

28. Horizontally place a nougat 1x3 tile on the 2<sup>nd</sup> row from the front (counting the 1<sup>st</sup> which is covered) on the 4<sup>th</sup> through 6<sup>th</sup> columns from the left (counting the entire build). Repeat symmetrically to the back.

29. Let's make 4 identical parts! Stack 2 grey 1x1 round plates with open stud. Then insert the bar of a grey 1x1 round plate with horizontal bar into the top open stud of the stacked plates. You should now have 4 identical parts! Place the first part on the 2<sup>nd</sup> row from the back (counting the back row which is covered) on the 3<sup>rd</sup> column from the left so the bar with the stacked pieces points to the left. Place the other parts on the other rows of the same column in the same way.

30. Horizontally place a grey 1x4 tile with 2 studs in front of you. Then horizontally place a dark tan 1x4 tile on the ppp. Place a grey 1x1 round plate with open stud under the rightmost column of the part. Repeat symmetrically to the left. Vertically place the sub build on the 3<sup>rd</sup> column from the left so it is centered vertically.

31. Let's make a part! Horizontally place a dark tan 1x2 plate in front of you.

32. Vertically place the back row of an orange 1x2 plate on the left column so one row overhangs to the front. Then horizontally place a dark tan 1x2 curved sloped tile on the back row so it slopes to the right and there is no overhang.

33. Orient a gray 2x2 corner plate so it looks like a braille letter h. place the right column underneath the front overhang so one column is exposed to the left.

34. Place a gray 2x2 left wedge plate on the left column so the point is in the back and on the left.

35. Vertically place a dark tan 2x3 left wedge plate on the ppp, so 1 row overhangs to the front.

36. Let's make a part! We will then attach this part to the previous one. Horizontally place a dark tan 1x3 plate in front of you. Horizontally place a grey 1x2 plate with 2 clips on the long side on the 2 left columns of the ppp so the clips face the front. The hands of the clips should point up to down. Then place the leftmost column of the part underneath the front overhang of the previous sub build. The clips should face the front.

37. Horizontally place a dark tan 2x3 curved left slope wedge tile on the 2 front rows on the 2 right columns so it slopes to the right. The point should be on the right and in the front.

38. Rotate the sub build 180 degrees so the clips face the back. Horizontally attach it on the 2 rows of front facing side studs at the left of the build.

Group 27:

39.1 Let's make a part! Stack 2 dark tan 1x2 plates and place them horizontally in front of you.

39.2 Horizontally place the plate of a dark tan 1x1 curved sloped brick with 1x1 plate on the right column of the ppp. Repeat symmetrically to the left.

39.3 Horizontally place a dark tan 1x2 tile on the ppps.

39.4 Turn the sub build upside down. place the 1x1 plate of a nougat 1x1 plate with 1x2 side studs hanging down on the leftmost column of antistuds. The side studs should face left and upright. Repeat symmetrically to the right.

39.5 Horizontally place a dark tan 1x2 curved inverted slope tile on the 2 right columns of the sub build so it slopes to the left. Repeat symmetrically to the left. Rotate the main build 180 degrees so the previous attached part faces the back right. Then flip the sub build so it sits on its front side. Rotate it 90 degrees clockwise so the side studs of the nougat 1x1 plates with 1x2 side studs hanging down face the front and the back. Place it over the 2 right columns of the front side studs located on the front right of the main build. Attach the back facing side studs of the part to the right 2 columns of front facing anti studs. The front facing side studs should rest above the 2x3 area of front facing side studs.

40. Let's make a part! Horizontally place a dark tan 1x2 plate in front of you.

41. Vertically place the back row of an orange 1x2 plate on the right column so one row overhangs to the front. Then horizontally place a dark tan 1x2 curved sloped tile on the back row so it slopes to the left and there is no overhang.

42. Orient a gray 2x2 corner plate so it looks like a braille letter J. place the left column underneath the front overhang so one column is exposed to the right.

43. Place a grey 2x2 right wedge plate on the rightmost column so the point is on the right and on the back.

44. Vertically place a dark tan 2x3 right wedge plate on the ppp, so 1 row overhangs to the front.

45. Let's make a part! We will then attach this part to the previous one. Horizontally place a dark tan 1x3 plate in front of you. Horizontally place a grey 1x2 plate with 2 clips on the long side on the 2 right columns of the ppp so the clips face the front. The hands of the clips should point up and down. Then place the rightmost column of the part underneath the front overhang of the previous sub build. The clips should face the front.

46. Horizontally place a dark tan 2x3 curved right slope wedge tile on the 2 front rows on the 2 left columns so it slopes to the left, and the point is on the left and on the front.

47. Rotate the sub build 180 degrees so the clips face the back. Horizontally attach it on the 3 rows of front facing side studs at the right of the build.

Group 28:

48.1 Let's make a part! Horizontally place a dark tan 1x2 plate in front of you. Horizontally place the right column of a dark grey 1x2 ingot tile on the left column of the ppp, So 1 column overhangs to the left.

48.2 Horizontally place the right column of a dark tan 1x4 hinge plate underneath the overhang so the round hinge part faces the front. Move the second plate on the left of the hinge so it points vertically to the front, and it forms a right angle.

48.3 Vertically place the 2 back rows of a dark tan 1,5x6x2 hand rail plate under the vertical 1x2 plate of the ppp so the hand rail faces left. Rotate the sub build 90 degrees clockwise so the hand rail faces the back and the first structure we build points vertically to the front. In this

position place the vertical structure of the sub build on the 3<sup>rd</sup> column of studs from the right so it is centered vertically,

49.1 Let's make a part! Horizontally place a dark tan 1x2 brick in front of you. Then place a grey 1x2 jumper plate on the ppp.

49.2 Place a grey 1x1 brick with side studs on 4 sides on the ppp. Vertically place a dark tan 1x1 roller skate on the ppp, so the rounded lip faces the front.

49.3 Place a nougat 1x1 round plate with bar on the left facing side stud so the bar points upright. Repeat symmetrically to the right.

49.4 Stack 2 dark tan roller skates so the rounded lip of the lower part faces the right and the one of the top part faces the left. Vertically place a dark tan 1x1 tile with 1x1 slope tile on top of the ppp, so it slopes to the front. Attach the ppp by the front antistud to the front facing side stud of the main sub build so the attached part slopes upward.

49.5 Vertically place the sub build on the second column of studs from the right so it is centered vertically then the part with the slop faces the left and rests on the ingot tile on the column to the left.

50. Horizontally place a dark tan 1,5x6x2 hand rail plate on the front row on the 4<sup>th</sup> through 9<sup>th</sup> columns from the right so the hand rail faces front. Then place a dark tan 1x2 tile horizontally on the 4<sup>th</sup> and 5<sup>th</sup> columns from the right on the front row. The front hand rail should be symmetrical to the back one you previously built.

51. Insert one end of a nougat 12L hose into the upward-facing clips at the right of the build on the front row. Curve the hose to the right, then connect the other end to the upward-facing clips on the back row. Both ends should point to the left, with the hose forming a smooth arc to the right.

52.1 Let's make 2 identical parts! Stack 3 transparent 2x2 round bricks with axle hole and insert a grey 3L bar into the axle hole. Push it down all the way through. You should now have 2 identical parts.

52.2 Turn the Desert Skiff upside down so the bow faces the left. Place the 1<sup>st</sup> part on the 2<sup>nd</sup> and 3<sup>rd</sup> columns of antistuds from the left so it is centered vertically. Then place the 2<sup>nd</sup> part on the 3<sup>rd</sup> and 4<sup>th</sup> columns of antistuds from the right so it is centered vertically.

53. Let's make a part! Stack 2 transparent 2x2 round bricks with axle hole. Insert a grey 3L bar into the axle hole all the way through. Place a transparent 4x4 round brick with 2x2 dome top under the ppps. Place a grey 2x2 round plate on top of the sub build. Attach the sub build to the antistuds of the main build, so it is centered vertically and horizontally.

54. Let's make a part! Horizontally place a dark tan 1x2 plate with 1x2 upright side studs in front of you, so the side studs face the front. Horizontally place a nougat 1x2 brick with pin hole on the 1x2 plate of the ppp, so the pin hole points back to front.

55. Horizontally place a nougat 1x2 plate with 4 side studs on top so the side studs face the front. Horizontally place a dark tan 1x2 slope tile on the ppp so it slopes to the back.

56. Horizontally place a grey 1x2 plate with 2 clips on the long side on the top row of front facing side studs, so it is centered horizontally. The clips should face up. Flip the sub build so it sits on its side, and the side studs face up and the clips point to the back.

57. Place a dark tan 3x6 half circle plate with 1x2 cut out on the top of the sub build so the rounded edge faces the front. 1 column overhangs to the left and right and 1 row overhangs to the front

58. Place the right column of a dark tan 1x2 curved tile on the left column of the front row so the curve faces the front left. Repeat symmetrically to the right. then place the front row of a gray 2x2 round tile with stud behind the 2 curved tiles.

59. Place a dark tan 1x2 tile horizontally to the left of the ppp on the back row. Place a dark tan 1x1 tile on the back row on the 2<sup>nd</sup> column from the right. Place a dark tan 1x2 curved slope tile horizontally to the right of the ppp, so 1 column overhangs to the right.

60. Place the 2 left columns of a dark tan 2x3 left wedge plate underneath the right overhang so the point faces the front left.

61. Horizontally attach the end with stop ring of a dark tan 6L bar with stop ring to the right clip, so the other end faces to the right. Repeat symmetrically to the left.

62. Place a nougat 1x1 round plate on the central stud of the 2x2 round tile with stud. Then place a dark tan conical Asian hat on the ppp.

63. Insert the pin of a 3l cylinder with hinge finger into the bottom facing pin hole so the hinge finger is vertical.

64. Turn the Desert skiff right side up so the bow faces the left. attach the bottom facing hinge of the sub build keeping the same position to the front facing hinge connector on the right side of the build.

Group 29:

65. Let's make a part! Horizontally place a dark tan 1x2 plate with 1x2 upright side studs in front of you, so the side studs face the front. Horizontally place a nougat 1x2 brick with pin hole on the 1x2 plate of the ppp, so the pin hole points back to front.

66. Horizontally place a nougat 1x2 plate with 4 side studs on top so the side studs face the front. Horizontally place a dark tan 1x2 slope tile on the ppp so it slopes to the back.

67. Horizontally place a grey 1x2 plate with 2 clips on the long side on the top row of front facing side studs, so it is centered horizontally. The clips should face up. Flip the sub build so it sits on its side, and the side studs face up and the clips point to the back.

68. Place a dark tan 3x6 half circle plate with 1x2 cut out on the top of the sub build so the rounded edge faces the front. 1 column overhangs to the left and right and 1 row overhangs to the front

69. Place the right column of a dark tan 1x2 curved tile on the left column of the front row so the curve faces the front left. Repeat symmetrically to the right. Then place the front row of a gray 2x2 round tile with stud behind the 2 curved tiles.

70. Place a dark tan 1x2 tile horizontally to the right of the ppp on the back row. Place a dark tan 1x1 tile on the back row on the 2<sup>nd</sup> column from the left. Place a dark tan 1x2 curved slope tile horizontally to the left of the ppp, so 1 column overhangs to the left.

71. Place the 2 right columns of a dark tan 2x3 right wedge plate underneath the left overhang so the point faces the front right.

72. Horizontally attach the end with stop ring of a dark tan 6L bar with stop ring to the right clip, so the other end faces to the right. Repeat symmetrically to the left.

73. Place a nougat 1x1 round plate on the central stud of the 2x2 round tile with stud. Then place a dark tan conical Asian hat on the ppp.



74. Insert the pin of a 3l cylinder with hinge finger into the bottom facing pin hole so the hinge finger is vertical.

75.1 Attach the bottom facing hinge of the sub build keeping the same position to the back facing hinge connector on the right side of the build. The Desert Skiff's build is complete!

75.2 Let's arrange the 2 builds and the minifigures for display. Place the Sarlacc Pit on the left. Vertically place the desert skiff 10 imaginary columns further to the right so the bow faces the front. Place Chewbacca, Lando and Han inside the desert skiff. Han Solo is close to the foldout railing. Luke is standing on the push-out plank. Place Boba Fett in front of the Sarlacc Pit looking to the front. Further to the front and centered place Nien Nunb on the commemorative platform looking to the front. Finally place a black 2x6 tile printed with the words You're gonna need a bigger boat in white lying flat horizontally between the Sarlacc Pit and the Desert skiff. The set is complete!

There are no ads at the end of the booklet.

Congratulations on finishing your build! Would you like to inspire other blind people to build LEGO sets? Let's feature your build on our [Builders page](#). It's easy and we will do all the work! Just contact us at [info@bricksfortheblind.org](mailto:info@bricksfortheblind.org) and together we will make it happen!

Please [signup](#) for our newsletter and follow us on [Facebook](#) and [Instagram](#) to be the first to know when new instructions are available!

Bricks for the Blind is a registered tax exempt 501(c)(3) corporation.