

76425 Hedwig at Privet Drive

Adapted by Arturo Moncada-Torres and tested by Natalie Charbonneau.

Nurture your youngster's love for the Wizarding World of adventures with this buildable fantasy toy for kids, featuring a model of Harry Potter's pet snowy owl Hedwig at 4 Privet Drive. The Hedwig owl figure has a posable head, wings and tail and can perch on the "Privet Drive" sign. This animal toy building set also includes a trunk containing assorted iconic Harry Potter items to enhance the display and inspire creative role-play.

The packaging feels like unopened wizard mail with deep tones of blue and green. The front of the box shows Hedwig perched happily on top of the classic "4 Privet Drive" sign, as well as the rest of the wizarding memorabilia laying to her right side: Harry's trunk, his wand with its corresponding box, his copy of "A History of Magic", and a picture of him as a baby and his parents. The background shows a stylized rendition of the Dursley's home with a foggy effect that adds to the street's mystery. The top edge is decorated with the iconic red LEGO® and the classic Harry Potter logos, as well as with a preview of the trunk with its tiny accessories. The left repeats a mosaic of Hedwig and the included accessories from slightly rotated angles, while the right side has the name of the set translated into 15 different languages. The back face depicts multiple shots that show Hedwig's posable features at the head, wings, and tail in action, as well as the trunk popping open with the book, wand, and portrait. The bottom edge is a tidy strip that contains the barcode as well as a few technical bits: the LEGO and Harry Potter logos, the set number, the recycling instructions for the paper/cardboard elements of the set, the place of manufacture, copyright and trademark notices, and a warning in many different languages that state that the set contains small parts and it is therefore not recommended for children younger than 3 years old.

The build consists of 337 pieces in total and is recommended for ages 7+.

Once finished, Hedwig is approximately 15 cm (6 in) tall and is 17 cm (7 in) wide with her wings widespread. The journey starts at Bag 1, where you will build the trunk's sturdy base. Bag 2 will bring the trunk to life with the trunk's lid and the wizarding relics. Bag 3 includes the pieces for Privet Drive's sign, preparing the stage for the star of the show, Hedwig, which you will put together with the contents of Bags 4, 5, and 6

Welcome to text-based instructions from Bricks for the Blind! Before you start building, here are some terms we may be using:

- In Front of/Front: towards you.
- Behind/Back: away from you.
- Up: towards the ceiling.
- Down: towards the floor.
- Stud: the bump on a LEGO brick. Example: A 2x1 brick has two studs on it.
- Vertically: with the longest side going from front to back
- Horizontally: with the longest side going from left to right.
- Upright: pointing up towards the ceiling.
- Standing upright: The piece is perpendicular to the ground, like a wall.
- Lying flat: The piece is parallel to the ground, like a piece of toast which fell off the table.
- That one/ppp: previously placed piece.
- Plate: piece with studs.
- Tile: smooth piece without studs (unless otherwise specified)

- A jumper plate is a 1x2 plate with a single stud on top, or a 1x3 plate with only two studs on top.
- “Anti-stud” is a term for the portion of a LEGO piece which accepts studs, like the bottom of a plate or brick.
- Symmetrically: a mirror image. Example: If you place a 2x1 brick with technic connector on the front wall at the right, connector to the front, and then place another such piece symmetrically on the back wall, at the right, the technic connector of the second piece should point to the back, since it will be placed symmetrically.
- Centered-vertically: even amount of space in front of and behind piece
- Centered-horizontally: even amount of space left and right of piece.
- Row: studs lined up horizontally (left to right/side to side).
- Column: studs lined up upright or vertically (top to bottom/back to front).

Additionally, it is worth mentioning that besides the printed visual instructions that come with each kit, a PDF version for the set's instructions is always available online at [<https://www.lego.com/en-en/service/building-instructions/76425>]. This might help a sighted building partner that may want to follow along or low vision users that may benefit from viewing the instructions on a personal device where they can zoom in on content and use assistive technologies to enhance the visuals.

Sorting the pieces:

To begin a successful build, it helps to sort the pieces into groups, bags, or small containers. Have a friend or family member do this in advance following the instructions below. You will see that the pieces should be sorted according to the building steps in the kit. Doing this in advance makes locating the pieces for each step easier. See below on how to sort the pieces to correspond to the steps in this set. Number the containers using letters A-Z, numbers, or meaningful names. The parts will be sorted into one or a small number of steps in the instructions. Example: Steps 1-3 means collect all the parts used in steps 1,2 and 3 and put them in one container.

This LEGO set comes with 6 bags labeled 1 through 6, one instruction booklet, and a sticker sheet. Sort the pieces into groups or piles as described below. Note that where there are multiple colors of the same brick in a step, the colors will be split into 2 groups to make telling the difference easier for the builder! LEGO includes a few spare parts in case you lose something. Set these into their own group away from the rest, in case you need them later.

Bag 1 – Trunk's base

- Group 1: Steps 1 - 9
- Group 2 - Steps 10 - 14
- Group 3 - Steps 15 - 17

Bag 2 – Trunk's lid and wizarding relics

- Group 4 – Steps 18 - 19
- Group 5 – Steps 20 - 24
- Group 6 – Steps 25 - 28
- Group 7 – Steps 29 – 35
- Group 8 – Steps 36 – 38

Bag 3 – Privet Drive's sign

- Group 9 – Steps 1 – 4

Group 10 – Steps 5 – 13
Group 11 – Steps 14 – 18

Bag 4 – Hedwig
Group 12 – Steps 1 – 9
Group 13 – Steps 10 – 14
Group 14 – Steps 15 – 22

Bag 5 – Hedwig
Group 15 – Steps 23 – 30
Group 16 – Steps 31 – 36
Group 17 – Steps 37 – 39
Group 18 – Steps 40 – 45
Group 19 – Steps 46 – 48

Bag 6 – Hedwig
Group 20 – Steps 49 – 54
Group 21 – Steps 55 – 59
Group 22 – Steps 60 – 66
Group 23 – Steps 67 – 74

All right, we are done with sorting. Let's get building!

Building Instructions

Book 1, bag 1:

Group 1 – Trunk's base

1. Locate 1 reddish brown 1x6 plate. Place it horizontally in front of you
2. Locate 2 reddish brown 2x2 tiles with two studs. Rotate them so that the studs are aligned horizontally and at the back. Then, place the back row on top of the 1x6 plate centered horizontally, so that each tile overhangs by one row to the front.
3. Locate 1 reddish brown 4x6 tile with studs on edges. Rotate it so that the edge with 6 studs is aligned horizontally and at the back. Then, place the back row under the overhang of the 2x2 tiles centered horizontally.
4. Locate 2 reddish brown 1x3 bricks. Place one vertically, on the back left corner of the assembly. Place the other symmetrically on the right side.
5. Locate 2 reddish brown 1x4 bricks. Place one vertically in front of the left previous piece, so it overhangs two studs to the front. Place the other symmetrically on the right side.
6. Locate 1 reddish brown 4x6 tile with studs on edges. Rotate it so that the edge with 6 studs is aligned horizontally and at the front. Place it under the overhang of the 1x4 bricks.

7. Locate 2 reddish brown 1x3 bricks. Place one vertically on the left column, so it overhangs one stud to the front. Place the other symmetrically on the right side.

8. Locate 1 reddish brown 1x6 plate. Place it horizontally under the overhang of the 1x3 bricks.

9. Locate 2 reddish brown 2x2 tiles with two studs. Rotate them so that the studs are aligned horizontally and at the front. Then, place the front row on top of the 1x6 plate centered horizontally, so that each tile has no overhang.

Group 2 – Trunk's base

10.1 Create the following subassembly twice: locate 1 reddish brown 1x4 plate and place it horizontally in front of you. Locate a 1x2 reddish brown plate and place it on top of the 1x4 plate centered horizontally.

10.2 Locate 2 dark bluish gray 1x1 inverted brackets. Rotate them so that the stud on the side is facing towards you. Put each inverted bracket on the free studs of the 1x4 plate.

10.3 Take one subassembly and rotate it so that its studs on the side are facing back. Place it on top of the free 1x4 space on the back row of the main assembly. Take the other subassembly and place it symmetrically on the front row.

11.1 Create the following subassembly. Locate 2 1x6 reddish brown plates. Place one on top of the other vertically.

11.2 Locate 3 reddish brown double curved 1x2 slopes. Place them vertically, to cover the 1x6 plates with them.

11.3 Place the subassembly on top of the left column of the main assembly by centering it vertically.

12. Locate 2 reddish brown 1x1 plates. Place one behind and one in front of the previous subassembly. Locate 2 reddish brown 1x2 plates. Place each of them horizontally behind and in front of the 1x1 plates, along the back and front rows of the main assembly.

13. Locate 2 reddish brown 1x4 bricks. Place each of them horizontally to the right of the 1x2 plates along the back and front rows of the main assembly.

14. Locate 2 reddish brown 1x3 bricks. Place each of them vertically along the right column of the main assembly, in front and behind the 1x4 bricks. Locate 1 reddish brown 1x2 brick with stud on the side. Place it vertically on the 1x2 space between the 1x3 bricks so that the stud on the side is facing right and outside the trunk's base.

Group 3 – Trunk's base

15. Locate 1 dark tan 1x6 tile. Place it vertically on top of the right column of the main assembly, centered vertically. Locate 2 dark tan 2x2 corner tiles. Place them on top of the right corners of the main assembly, next to the 1x6 tile. There should be no overhang.

16. Locate 2 reddish brown 1x4 double curved slopes. Rotate the first one horizontally and so that the antistud is facing towards you. Place it on top of the studs on the side along the face of the main assembly that is farthest from you. Rotate and place the second one symmetrically along the face of the main assembly that is closest to you.

17. Locate 1 light bluish gray 1x2 round plate with open studs. Rotate it vertically upright so that the studs are facing to your right. Place the bottom antistud of the plate on the stud along the right side of the main assembly, so the top stud overhangs to the top. Locate 1 light bluish gray 1x1 tile with black keyhole pattern. Place it on the bottom stud of the 1x2 round plate.

Book 1, bag 2:

Group 4 – Trunk's lid

18. Locate 1 reddish brown 8x12 plate. Place it vertically in front of you.

19. Locate 2 reddish brown 1x4 plates. Place them horizontally on the front and back rows of the 8x12 plate centered horizontally. Locate 2 reddish brown 1x2 plates. Place them horizontally on top of the 1x4 plates centered horizontally.

Group 5 – Trunk's lid

20. Locate 2 dark tan 1x2 plates. Place them vertically on top of the 8x12 plate on the 2nd and 5th columns from the left centered vertically.

21. Locate 2 reddish brown 1x10 plates. Place them vertically on top of the free studs of the 1x4 plates. The 1x10 plates will also be on top of the 1x2 dark tan plates from the previous step.

22. Locate 1 dark tan 1x2 plate. Place it horizontally on top of the 1x2 plate that is on the back row. Locate 2 dark tan curved 2x1 curved slopes with recessed studs. Place them horizontally on the corners of the row to the back so that the curved slope faces outwards.

23. Locate 1 reddish brown 2x4 tile. Place it horizontally one row in front of the back row centered horizontally. Locate 2 reddish brown 1x2 curved slope bricks. Place them vertically left and right of the 2x4 tile with the curved edges facing outwards.

24.1 Locate 2 dark tan curved 2x1 curved slopes with recessed studs. Place them horizontally in front of the slopes from the previous step with the curved edges facing outwards. Locate 2 reddish brown 1x2 curved slope bricks. Place them vertically in front of the previously placed slopes with the curved edges facing outwards. Locate 2 dark tan curved 2x1 curved slopes with recessed studs. Place them horizontally in front of the previously placed slopes with the curved edges facing outwards

Group 6 – Steps 25 – 28

25. Locate 2 dark bluish gray 1x2 bricks. Place them horizontally on the 4th and 7th rows from the front, which correspond to the spaces between the curved slopes with recessed studs.

26.1 Locate 2 reddish brown 1x2 curved slope bricks. Place them vertically on the leftmost and right most columns with the curved edges facing outwards, leaving the studs of the front row free. Locate a 2x4 reddish brown tile. Place it horizontally between the 1x2 curved slopes.

27. Locate a 1x2 dark tan plate. Place it horizontally on top of the front row centered horizontally. Locate 2 dark tan curved 2x1 curved slopes with recessed studs. Place them horizontally with the curved edges facing outwards on the corners of the front row.

28. Locate 4 dark tan 1x4 tiles. Place them horizontally on top of all horizontal 1x4 free studs

Group 7 – Steps 29 – 35

29.1 Flip the assembly upside down from left to right. Locate 2 dark bluish gray plates modified with pin hole on bottom. Rotate them horizontally and flip them upside down, making sure that the pin hole is on the right side. Take one and place it on the 2nd row from the front and on the rightmost column, leaving no overhang. Take the second one and place it on the 2nd row from the back and on the rightmost column, leaving no overhang. Locate 2 reddish brown 1x1 plates. Flip them upside down. Place one of them on the 2nd column from the right and the 3rd row from the front. Place the other one on the 2nd column from right on the 3rd row from the back.

30. Locate 2 dark bluish gray 2x2 inverted slopes. Flip them upside down and place each of them on top of the plates with holes and the 1x1 plates, making sure that they also connect with the 6x10 plate.

31. Locate 2 black technic pins. Take one and place it from the front into the front pin hole. Put the second pin symmetrically through the back pin hole. The free segment of the pins should be facing front and back.

32. Create the following subassembly twice. Locate 1 reddish brown 1x2 modified plate with pin hole on top and 1 reddish brown 1x1 plate. Place the plate on top of the stud of the modified plate. Flip the subassemblies upside down. Rotate them horizontally so that the pin hole is at the right and put them through the technic pins.

33. Flip the trunk's lid subassembly upside down from left to right. Place it on top of the subassembly of the trunk's base.

34.1 Open the trunk as much as possible. Locate 2 dark tan 1x3 tiles. Place them horizontally on the studs along the front and back rows of the trunk's base.

35.1 Locate a 2x4 reddish brown tile. Place it horizontally in front of you.

35.2 We need to apply a sticker. Apply sticker number 6 (a reddish brown sticker with the Hogwarts coats of arms, which is made of the coats of arms of all four houses together: Slytherin, Ravenclaw, Hufflepuff, and Gryffindor) horizontally across the tile. Ask a sighted friend to make sure that the sticker is applied and oriented correctly.

35.3 Close the trunk. Place the stickered tile on the only empty space on the top of the trunk's lid. With this, we finish the build of the trunk. Great!

Group 8 – Steps 36 – 38

36.1 Time to assemble some magical objects. Locate a tan 1x4x3 brick. Rotate it vertically and flip it to the side so that the studs face to the left.

36.2 We need to apply a sticker. Apply sticker number 5 (a tan sticker with the cover of “A History of Magic” book – a very important read for all Hogwarts students!). Ask a sighted friend to make sure that the sticker is applied and oriented correctly.

36.3 Locate a 1x4 tan tile and use it to cover the 1x4x3 brick’s studs.

36.4 “A History of Magic” is done! Place it inside the trunk.

37.1 Now we will create Harry’s family photo. Locate a 2x3 dark tan tile and place it horizontally in front of you.

37.2 We need to apply a sticker. Apply sticker number 4 (a tan sticker with a the minifigure version of a photo of Harry’s parents holding him as a baby). Ask a sighted friend to make sure that the sticker is applied and oriented correctly.

37.3 The heart-warming photo is done! Place it inside the trunk.

38.1 No Hogwarts student would be complete without a magical wand. Let’s put together one, starting with a wand box. Locate a 1x8 tan plate. Place it horizontally in front of you.

38.2 Locate 2 tan 1x3x1 panels. Place them horizontally on top of the 1x8 plate centered horizontally with the angled surface towards you.

38.3 Locate 2 tan 1x1 modified bricks with stud on the side. Place them next to the panels on top of the empty studs of the 1x8 plate so that their studs on the side are facing you.

38.4 Locate a 1x8 tan tile and place it on top of the 1x1 modified bricks with stud on the side.

38.5 Flip the subassembly so that the empty space is facing upwards. Locate 1 reddish brown 4L lightsaber blade and place it into the 1 dark brown candle utensil to make a powerful wand. Place the wand inside the wand box.

38.6 Locate a 1x8 dark orange tile and place it on top of the free studs of the 1x1 modified bricks, closing the wand box.

38.7 Your wand is done. Place it inside the trunk. Now your trunk is ready for your first day at Hogwarts!

Book 1, bag 3:

Group 9 – Steps 1 – 4

1. We will now build Privet Drive's sign, where Hedwig will be gracefully posed later. Let's start with the base. Locate 1 green 1x6 plate. Place it horizontally in front of you. Locate 1 green 3x1 inverted slope brick. Place it horizontally, sloping to the left, with the rightmost stud on top of the leftmost stud of the 1x6 plate, so that the slope brick overhangs the plate by two studs.

2. Locate 1 green 1x3 brick. Place it horizontally next to the 3x1 inverted slope. Locate 1 reddish brown 1x1 brick with stud on the side. Place it next to the 1x3 brick so that its stud on the side is facing you. Locate 1 green 3x1 inverted slope brick. Place it horizontally, sloping to the right, with the leftmost stud on top of the rightmost stud of the 1x6 plate, so that the slope brick overhangs the plate by two studs.

3. Locate 1 green 1x10 plate. Place it horizontally on top of the subassembly, centered horizontally.

4. Locate 1 green 1x1 brick and place it on top of the 1x10 plate on the third stud from the left. Locate 1 reddish brown 1x1 brick with stud on the side. Place it to the right of the 1x1 brick so that the stud on the side is facing to the front. Locate 1 green 1x4 brick. Place it horizontally to the right of the 1x1 reddish brown brick with stud on the side.

Group 10 – Steps 5 – 13

5. Let's build the actual sign. Locate 1 black 2x8 plate. Place it horizontally in front of you. Locate 1 black 2x6 plate. Place it horizontally on top of the 2x8 plate centered horizontally.

6. Locate 1 black 2x2 plate and place it on top of the 2x6 plate centered horizontally.

7. Locate 2 black 1x2 plates. Place each of them horizontally to the left and right of the 2x2 plate on the back row. Locate 2 black 1x2 plates with clip on side. Place them horizontally to the left and right of the 2x2 plate on the front row with the clips facing front.

8.1 Create the following subassembly (the sign's legs) twice. Locate 1 black 1x8 plate and place it vertically in front of you. Locate 1 light bluish gray 1x1 round plate and place it on top of the 1x8 plate on the backmost stud.

8.2 Locate 1 light bluish gray round plate and place it on top of the round plate of the previous step.

8.3 Locate 1 black 1x4 half circle curved slope brick. Place it vertically on top of the 1x8 plate, to the front of the 1x1 round plates. This will leave three studs free to the front.

8.4 The sign's legs subassemblies are complete. Place them vertically on top of the free studs at the left and right columns of the previous subassembly (which is oriented horizontally) so that only one stud overhangs towards you.

9. Locate 2 black 2x2 plates. Take the first one and place its right column on top of the sign's left leg's free studs, to the front of the curved slope bricks. This will leave the 2x2 plate with a 1x2 overhang to the left. Take the second 2x2 plate and place it symmetrically on the right side.

10.1 Locate 1 white 2x6 tile. Place it horizontally in front of you.

10.2 We need to apply a sticker. Apply sticker number 1 (a white sticker of the street sign with the text “Privet”). Ask a sighted friend to make sure that the sticker is applied and oriented correctly.

10.3 Place the tile with the sticker on top of the sign subassembly flush with the right side, on top of the right 2x2 plate of the previous step.

11.1 Locate 1 white 2x4 tile. Place it horizontally in front of you.

11.2 We need to apply a sticker. Apply sticker number 3 (a white sticker of the street sign with the text “Drive”). Ask a sighted friend to make sure that the sticker is applied and oriented correctly.

11.3 Place the tile with the sticker on top of the sign subassembly on the remaining free studs, flush with the left side.

12. Locate 2 black 1x1 curved slopes. Place them on top of the free studs to the front of the “Privet Drive” tiles so that one of their flat faces is facing to the front.

13. We will now attach the sign to the base that we have so far. To do so, place the backmost edge of the sign (with the 1x1 round plates) on top of the base centered horizontally, flush.

Group 11 – Steps 14 – 18

14. We now have the (partially constructed) base with the sign together. Let’s finish the rest of the base. Locate 2 green 1x1 bricks and place them on the free studs on the left and right sides of the back row.

15. Locate 1 green 1x6 brick. Place it horizontally on top of the base’s back row, centered horizontally. Be careful that the sign doesn’t pop out. Next, locate 2 green 1x2 slopes. Place each of them horizontally to the left and right of the 1x6 brick, making sure that the slopes face outwards.

16. Locate 1 green 1x2 slope. Place it horizontally on top of the base’s back row on the leftmost 2 studs with the slope facing outwards. Locate 1 green 1x2 brick. Place it horizontally to the right of the 1x2 slope. Locate 1 reddish brown 1x1 brick with stud on the side. Place it to the right of the 1x2 brick so that the stud on the side is facing to the front. Locate 1 green 1x3 brick. Place it horizontally to the right of the ppp.

17.1 We will create a small subassembly to round off the sign’s base. Locate 1 green 1x3 plate. Place it horizontally in front of you.

17.2 Locate 1 green 3x1 curved slope. Place it horizontally on top of the 1x3 plate on the leftmost column so that the curved slope is facing to the left. Locate 1 green 1x1 plate and place it on top of the 1x3 plate, to the right of the 3x1 curved slope.

17.3 Locate 1 green 3x1 curved slope. Place it horizontally symmetrically to the 3x1 curved slope of the previous step. Locate 1 green 1x1 tile and place it on the remaining free stud.

17.4 Place this subassembly on top of the base, centered.

18. Flip the sign so that it rests on the base and the sign's tiles with the stickers that say "Privet Drive" face towards you. Locate 3 bright light orange flowers and place them on the free studs at the base to give the sign some nice botanical touch. Awesome! The sign is finished.

Book 1, bag 4:

Group 12 – Steps 1 – 9

1. Let's start with the star of the show: Hedwig! More specifically, let's build her torso and legs. Locate 1 white 1x6 plate. Place it horizontally in front of you. Locate 1 white 1x2 plate with bar handles on side. Place it horizontally on top of the 1x6 plate on the leftmost two studs so that the handle is facing towards the back.

2. Locate 1 white 1x2 plate with bar handles on side. Place it symmetrically to the last piece on the right side. Locate 1 white 2x2 plate and place it on top of the 1x6 plate, between the two previous pieces so that the 2x2 plate has a 1x2 overhang to the front.

3. Locate 1 white 4x4 plate and place it under the 2x2 plate overhang centered horizontally.

4. Locate 2 dark bluish gray 1x3 plates. Place them vertically on top of the 4x4 plate on the left and right columns on the backmost 3 studs, leaving one free stud to the front. Locate 2 dark bluish gray 1x2 plates with tow ball on side. Place them vertically in front of the 1x3 plates, leaving them with a one stud overhang towards you and making sure that the tow balls are facing outwards.

5. Locate 2 dark bluish gray 1x3 plates. Place them vertically on top of the 1x2 plates with tow balls so their front is even with the front of the 1x2 plates with tow balls. Locate 2 light bluish gray 2x3 plates. Place them vertically to the back of the 1x3 plates, centered horizontally.

6. Locate 2 white 1x2 curved slopes. Take the first one and rotate it horizontally so that the slope is facing to the left. Place the leftmost stud of the slope on top of the free stud of the 1x2 plate with bar to the left. Take the second one and place it symmetrically to the right.

7. Locate 2 light bluish gray 1x2 plates. Place the first one horizontally between the curved slopes. Place the second one horizontally two rows in front of the previous piece, centered horizontally. Locate 1 white 1x4 plate. Place it horizontally between the 1x2 plates centered horizontally.

8. Locate 1 white 2x2 brick with ball socket and axle hole. Place it to the front of the 1x2 plate on the large 2x2 space so that the socket is facing to the front.

9. Locate 2 white 1x4 plates. Place them vertically to the left and right of the 2x2 brick with ball and socket. They should have no overhang.

Group 13 – Steps 10 – 14

10. Flip the assembly upside down from left to right. The ball socket should be closest to you. Locate 2 white 2x2 corner plates. Rotate them so that their studs are facing downward. Take the first one and rotate it so that it looks like a D in Braille and place it on the backmost row, to the left. Take the second one and rotate it so that it looks like an F in Braille and place it symmetrically to the right. They should have no overhang.

11. Locate 1 white 2x4 plate. Rotate it vertically and flip it so that its studs are facing downwards. Place it on the second row from the back, centered horizontally. The first row of the 1x4 plate should be between the 2x2 corner plates. Locate 2 light bluish gray 1x2 inverted curved slopes. Rotate them vertically and flip them so that the studs are facing downwards and the slopes towards the front. Place them on the left and right studs of the front row. They should have no overhang.

12. Locate 1 white 2x2 plate. Flip it so that its studs are facing downwards. Place it between the 1x2 inverted curved slopes. It should have no overhang. Locate 2 light bluish gray 1x2 plates with locking hinge. Rotate them vertically so that the locking hinges are facing towards the back and flip them so that the studs are facing downwards. Place them behind the 2x2 plate, centered horizontally.

13. Locate 1 white 4x2 inverted slope with 2x2 cutout. Flip it so that its studs are facing downwards and place it horizontally on the third row from the back, on top of the front row of the 1x2 plates with locking hinge and on top of the back row of the 2x2 plate.

14. Locate 2 light bluish gray 1x2 inverted curved slopes. Flip them so that the studs are facing downwards and place them horizontally to the back of the 4x2 inverted slope with cutout, covering the remaining stud of the plates with locking hinge. Make sure that the curved slopes are facing outwards and that they have no overhang.

Group 14 – Steps 15 – 22

15. Flip the assembly right-side up from left to right. The ball socket should be closer to the front. Locate 1 white 4x2 slope. Place it vertically on the third row from the back, making sure that the slope is facing to the back. The slope should have one row overhang to the back. Locate 2 white 1x2 slopes. Place them vertically to the left and right of the 4x2 slope where there are studs, making sure that the slopes face outwards. They should have no overhang.

16. Locate 2 white 2x2 slopes. Place them to the front of the 4x2 and 1x2 slopes, centered horizontally, making sure that the slopes are facing outwards. Locate 2 white 1x1 plates. Place them on the studs to the front of the 2x2 slopes.

17. Locate 2 white 1x1 slope tiles. Place them on top of the 1x1 plates of the previous steps, making sure that the slopes are facing outwards.

18. Locate 1 white 2x2 plate. Place it on top of the studs of both 2x2 slopes centered horizontally.

19. Locate 1 white 1x2 modified plate with claws. Place it on top of the back row of the 2x2 plate from the previous step so that the claws are facing away from you.

20.1 We need to make a small subassembly. Locate 1 white 2x2 curved slope. Place it in front of you so that the slope is facing to the front. Locate 1 light bluish gray 1x2 plate. Place it horizontally under the front row of the 2x2 slope.

20.2 We need to apply a sticker. Apply sticker number 2 (a white sticker with some fluffy feather texture) on top of the 2x2 curved slope. Ask a sighted friend to make sure that the sticker is applied and oriented correctly

20.3 Place the subassembly to the front of the 1x2 plate with claws, making sure that the edge of the slope with the 1x2 plate is facing towards you and has a 1x2 overhang (on top of the ball socket).

21.1 We will create the following subassembly twice, which corresponds to Hedwig's talons. Locate 1 white 1x2 plate with open clips. Rotate it horizontally and flip it so that the studs are facing downwards and the clips towards you. Locate 1 white 1x2 round plate with open studs. Rotate it horizontally and flip it so that the studs are facing downwards. Place it on top of the 1x2 plate with clips.

21.2 Locate 2 dark tan claws and place them into the holes of the 1x2 round plate, making sure that the curve is facing towards the clips.

21.3 Flip the talons subassemblies right-side up from left to right so that the claws are facing away from you and the studs are facing upwards. Clip them to the handles located on the row to the back of the main assembly.

22. Angle the talons so that the claw pieces are facing upwards as much as possible. We are done with the torso, nice!

Book 1, bag 5:

Group 15 – Steps 23 – 30

23. Let's continue with Hedwig's tail. Locate 1 white 1x4 plate. Place it horizontally in front of you.

24. Locate 2 white 1x2 plates with locking finger. Rotate them vertically so that the locking finger is at the back. Place their back stud on top of the 1x4 plate, centered horizontally. Each 1x2 plate will be left with a one stud overhang to the front.

25. Locate 1 white 2x4 wedge plate. Place it under the overhang of the 1x2 plates with locking finger so that the wide part is at the front.

26.1 Put together the following subassembly twice (each will be a tail feather). Locate 1 light bluish gray 1x2 plate. Place it vertically in front of you.

26.2 Locate 1 light bluish gray 1x3 round plate with open studs. Place it vertically on top of the 1x2 plate on the back stud, leaving the front stud of the 1x2 plate free and with 2 studs of the 1x3 round plate overhanging to the back.

26.3 Locate 1 white 1x2 curved slope. Place it vertically on top of the front stud of the 1x2 plate and the front stud of the 1x3 round plate so that the slope is facing towards you. The tail feather subassemblies are done!

26.4 Connect each subassembly with the main tail assembly by placing the subassemblies' back stud to the left and right of the 1x2 plates with locking fingers. Rotate them so that they are as close as possible to the 2x4 wedge plate.

27. Locate 1 white 1x4 tile. Place it horizontally on top of the back row.

28. Locate 2 black quarter round tiles. Take the first one and place it on the stud that is free on the left side, between the 1x4 tile and the 1x2 slopes. Make sure that its curved side is facing outwards and to the back. Take the second quarter round tile and place it symmetrically on the right side.

29. Locate 2 white 1x4 curved slopes. Place them vertically on the free studs at the center so that the slopes are facing towards you, making sure that they have two studs overhanging to the front.

30. Take the main assembly (Hedwig's torso) and rotate it so that the surface with studs (her chest) is facing downwards and the tow balls are facing left and right, closer to the back. Take the tail subassembly, make sure that the tile surface is facing upwards, and connect it to the torso with the locking fingers. Raise the tail one notch. We are done with the tail!

Group 16 – Steps 31 – 36

31. We will now start with the wings. More specifically, with the wing-to-the-right. Locate 1 white 3x3 plate with round corner. Place it in front of you so that the round corner is facing to the front and to the left. Locate 1 light bluish gray 1x2 plate with ball socket on side. Place it vertically on the right column of the 3x3 plate with round corner to the back (without any overhang) and with the socket facing right.

32. Locate 1 light bluish gray 1x2 plate. Place it vertically to the left of the 1x2 plate with ball socket.

33. Locate 4 black 1x1 round plates with bar handle. Place each of them on top of the free studs of the 3x3 plate with round corner. Make sure that the handles are facing outwards and that they follow the plate's curve.

34. Locate 1 white 3x3 plate with round corner. Place it on top of the wing's subassembly so that the round corner is facing to the front and to the left.

35. Locate 2 black quarter round tiles. Place them on the studs that are along the 3x3 plate's curve so that the tiles' curve is facing to the front and to the left.

36.1 We will create the following subassembly twice (which will be two long feathers). Locate 1 light bluish gray 1x2 plate. Place it horizontally in front of you. Locate 1 white 1x1 plate with open clip. Place it on top of the right stud of the 1x2 plate so that the clip is facing to the right.

36.2 Locate 1 white 1x4 curved slope. Rotate it horizontally and place the 1x2 plate and 1x1 plate with clip under the curved slope, filling the space under it. The long feathers are done!

36.3 Attach each of the long feathers onto the wing by connecting the clips to the left-most handles.

Group 17 – Steps 37 – 39

37.1 We will create the following subassembly twice (which will be two short feathers). Locate 1 light bluish gray 1x2 plate. Place it horizontally in front of you. Locate 1 white 1x1 plate with open clip. Place it on top of the right stud of the 1x2 plate so that the clip is facing to the right.

37.2 Locate 1 white 1x2 curved slope. Rotate it horizontally and place the 1x2 plate and 1x1 plate with clip under the curved slope, filling the space under it. The short feathers are done!

37.3 Attach each of the short feathers onto the wing by connecting the clips onto the rest of the free handles.

38. Flip the wing upside down. Locate 1 white round 2x2 plate with rounded bottom and place it on top of the 3x3 plate with round corner centered horizontally and vertically.

39. Take the wing-to-the-right assembly and connect it to Hedwig's torso. Make sure that her claws are facing downwards and that the studs on her chest are facing front. Make sure that the wing's studded surface is facing to the back and that the tow ball is facing to the left. Connect the wing using the wing's ball socket and the torso's right tow ball. You can pose the wing as you wish. We are done with the wing-to-the-right!

Group 18 – Steps 40 – 45

40. We will continue with the other wing – the wing-to-the-left. The assembly is the same as the other wing but mirrored. Let's begin. Locate 1 white 3x3 plate with round corner. Rotate it so that the round corner is facing front to the right. Locate 1 light bluish gray 1x2 plate with ball socket on side. Place it vertically on the left column of the 3x3 plate with round corner to the back (without any overhang) and with the socket facing left.

41. Locate 1 light bluish gray 1x2 plate. Rotate it vertically and place it to the right of the 1x2 plate with ball socket.

42. Locate 4 black 1x1 round plates with bar handle. Place each of them on top of the free studs of the 3x3 plate with round corner. Make sure that the handles are facing outwards and that they follow the plate's curve.

43. Locate 1 white 3x3 plate with round corner. Place it on top of the wing's subassembly so that the round corner is facing towards you and towards the right.

44. Locate 2 black quarter round tiles. Place them on the studs that are along the 3x3 plate's curve so that the tiles' curve is facing front and to the right.

45.1 We will create the following subassembly twice (which will be two long feathers). Locate 1 light bluish gray 1x2 plate. Place it horizontally in front of you. Locate 1 white 1x1 plate with open clip. Place it on top of the left stud of the 1x2 plate so that the clip is facing to the left.

45.2 Locate 1 white 1x4 curved slope. Rotate it horizontally and place the 1x2 plate and 1x1 plate with clip under the curved slope, filling the space under it. The long feathers are done!

45.3 Attach each of the long feathers onto the wing by connecting the clip to the right-most handles.

Group 19 – Steps 46 – 48

46.1 We will create the following subassembly twice (which will be two short feathers). Locate 1 light bluish gray 1x2 plate and place it horizontally in front of you. Locate 1 white 1x1 plate with open clip. Place it on top of the left stud of the 1x2 plate so that the clip is facing to the left.

46.2 Locate 1 white 1x2 curved slope. Rotate it horizontally and place the 1x2 plate and 1x1 plate with clip under the curved slope, filling the space under it. The short feathers are done!

46.3 Attach each of the short feathers onto the wing by connecting the clip with the rest of the free handles.

47. Flip the wing upside down. Locate 1 white round 2x2 plate with rounded bottom and place it on top of the 3x3 plate with round corner centered horizontally and vertically.

48. Take the wing-to-the-left assembly and connect it to Hedwig's torso. Make sure that her claws are facing downwards and that the studs on her chest are facing front. Make sure that the wing's studded surface is facing to the back and that the tow ball is facing to the right. Connect the wing using the wing's ball socket and the torso's left tow ball. You can pose the wing as you wish. We are done with both wings!

Book 1, bag 6:

(The LEGO instructions have a small mistake and omit when to open Bag 6. You should open it at this point).

Group 20 – Steps 49 – 54

49. Time for the last element of Hedwig: the head! Locate 1 white 4x4 plate and place it in front of you. Locate a 1x2 light bluish gray plate. Place it horizontally on top of the 4x4 plate on the back row, centered horizontally.

50. Locate 2 black 1x3 jumper plates. Place them vertically to the front of the 1x2 plate, centered horizontally. The 4x4 plate should have one complete column of studs free at both the leftmost and rightmost sides.

51. Locate 1 red 1x2x2 brick with studs on the side. Rotate it so that the studs on the side are facing to the back place it centered horizontally on the back row, on top of the 1x2 plate. Locate 1 white 2x2 brick with ball joint. Rotate it so that the ball join is to the front and place it on top of all four studs of the 1x3 jumper plates.

52. Locate 2 light bluish gray 1x4 bricks. Place them vertically on the left and right columns.

53. Locate 4 white 1x2x2 brackets. Place them on top of the 1x4 bricks so that the studs on the side are facing outwards.

54. Locate 2 dark bluish gray 1x2 jumpers. Place them vertically on top of the studs of the 2x2 brick with ball joint.

Group 21 – Steps 55 – 59

55. Locate 2 green 1x2 plates. Place them vertically on top of the leftmost and rightmost columns centered vertically. Locate 4 white 1x1 inverted brackets and place them on the free studs of the left and right columns, making sure that the studs on the side are facing outwards, to the left and right.

56. Locate 2 light bluish gray 1x1x2 brackets. Place them on the corners of the back row, making sure that the studs on the side are facing to the back. Locate 2 light bluish gray 2x3 plates. Place them vertically and centered so that all the elements of the top layer of the head subassembly are at the same level.

57. Locate 1 white 2x2 plate and place it on top of the head subassembly centered horizontally and vertically. Locate 2 1x4 plates. Place them horizontally on the front and back rows.

58. Locate 4 white 2x1 curved slopes with recessed studs. Place them horizontally to the left and right of the 2x2 plate, making sure that the slopes are facing outwards.

59. Locate 2 dark bluish gray 1x2 jumpers. Place them vertically on the leftmost and rightmost columns centered vertically. Locate 1 white 1x4 plate. Place it horizontally on top of the back row.

Group 22 – Steps 60 – 66

60. Locate 1 white 1x2 jumper. Place it horizontally to the front of the 1x4 plate. Locate 1 white 1x2 tile. Place it horizontally to the front of the 1x2 jumper. Locate 1 white 1x2 jumper. Place it horizontally to the front of the 1x2 tile.

61. Locate 2 white 1x1 round quarter tiles. Place them on the corners that are at the front left and front right, making sure that the curved parts are facing to the front and outwards.

62. Flip the subassembly 90 degrees from right to left. The antistuds should be facing to the right and the ball joint to the front. Locate 1 white 1x4 double curved slope. Place it vertically on top of the studded surface centered horizontally. Locate 2 white 1x1 round quarter tiles. Place them on the corners that are to the left, making sure that the curved parts are facing to the left.

63. Flip the subassembly 180 degrees from right to left. The antistuds should be facing to the left and the ball joint to the front. Locate 1 white 1x4 double curved slope. Place it vertically on top of the studded surface centered horizontally. Locate 2 white 1x1 round quarter tiles. Place them on the corners that are to the right, making sure that the curved parts are facing to the right.

64. Flip the subassembly 90 degrees from left to right. The antistuds should be facing upwards. Create the following small subassembly twice. Locate 1 white 1x2 plate with 3 teeth. Place it in front of you so that the teeth are facing towards you. Locate 1 white 1x4 double curved slope. Place it horizontally on top of the 1x2 plate with 3 teeth. The small subassemblies are complete. Rotate them so that the teeth are facing upwards and place each of them on the left and right studded surfaces.

65. Locate 1 white 2x4 plate. Rotate it vertically and flip it so that the antistuds are facing upwards. Place it on top of the head subassembly centered horizontally.

66. Locate 4 white 2x2 inverted curved slopes. Place them on top of the head subassembly, making sure that the slopes are facing left and right.

Group 23 – Steps 67 – 75

67. Rotate the head subassembly 180 degrees from top to bottom. The slopes of the previous step should be facing downwards, and the ball joint should be facing to the back. Locate 1 white 2x2 plate and place it centered horizontally on the front-facing studs.

68. Locate 2 white 1x4 double curved slopes. Place them vertically on top of the 2x2 plate of the previous step.

69. Locate 4 white 1x1 round quarter tiles. Place them on the free studs of the face that is closest to you, making sure that the curved parts are facing upwards and outwards.

70. Locate 1 white 1x2 slope. Place it horizontally on the top face on the front row centered horizontally, making sure that the slope is facing to the front. Locate 2 white 1x1 round quarter tiles. Place them to the left and right of the 1x2 slope, making sure that the curved parts are facing front and outwards.

71. Rotate the head subassembly 180 degrees from left to right. The ball joint should be facing front. Locate 1 light bluish gray 1x1 plate and place it next to the 1x2 slope from the previous step. Locate 1 white 1x1 tile and place it on top of the 1x1 plate.

72.1 In this step we will put together Hedwig's beak subassembly. Locate 1 white 1x1 inverted bracket and place it in front of you. Locate 1 white 1x1 tile and place it on top of the bracket.

72.2 Locate 1 black 1x1 plate with vertical tooth. Rotate it so that the stud is facing front, and the tooth is facing upwards and place it on the stud on the side of the bracket.

72.3 Locate 1x1 white tile and place it on top of the stud of the 1x1 plate with tooth. The beak is complete!

72.4 Take the beak subassembly and rotate it vertically. The antistud at the bottom should be closest to you. Place it on top of the head subassembly centered horizontally.

73. Take the 2 bright light orange round tiles with eye pattern and place each of them to the left and right of the beak. Ask a sighted friend to make sure that the eyes are oriented correctly, otherwise Hedwig might look a bit cross-eyed.

74. The head subassembly is complete! Time to connect it with Hedwig's body. Do so by putting the ball joint into the ball socket of the body. It might need a bit of strength to make sure that the ball joint goes in, but be careful not to go too far. Make sure that both the studded surface of Hedwig's chest and the beak of Hedwig's head are facing front. Hedwig is done!

75. For the last step, we need to perch Hedwig on top of the Privet Drive's sign. You can do so by connecting the bars behind Hedwig's talons with the clips on top of Privet Drive's sign. Feel free to pose Hedwig's head and wings as you wish. Don't move the tail too much, though, since it helps Hedwig stay balanced on the sign. Also, don't forget to showcase the trunk and its magical contents!

At the end of the instruction booklet, you will find the set inventory and an invite to share feedback, no advertisements for other sets.

Congratulations on finishing building "Hedwig at 4 Privet Drive"! Thank you so much for building this set.

Would you like to inspire other blind people to build LEGO sets? Let's feature your build on our [Builders page](#). It's easy and we will do all the work! Just contact us at info@bricksfortheblind.org and together we will make it happen!

Please [signup](#) for our newsletter and follow us on [Facebook](#) and [Instagram](#) to be the first to know when new instructions are available! We also love seeing your completed builds, so please tag our Facebook and Instagram accounts in any photos of your builds so we can share your accomplishments with our Bricks for the Blind community.

Bricks for the Blind is a registered tax exempt 501(c)(3) corporation.