

77239 Porsche 911 GT3 RS Super Car

Set adapted by Alex Charbonneau and tested by Natalie Charbonneau.

Boys and girls aged 9 and up can collect, build, play with and display this sleek LEGO® Speed Champions (77239) Porsche 911 GT3 RS Super Car toy. The latest model in one of the most iconic series of sports cars, this brick-built mini car replica for kids features many famous details from the real-life vehicle that is driven on both the street and the track.

This Porsche 911 GT3 RS toy includes its famous rear wing, air intake features on the hood, distinctive headlights and novelty rims. The LEGO car set also comes with a driver minifigure in a helmet and red Porsche Track Day Experience outfit. Kids can place the minifigure behind the wheel and stage their own track-day racing action.

LEGO Speed Champions building sets let kids and passionate car fans build replica versions of some of the world's most iconic vehicles. Each car playset can be created using the LEGO Builder app, which guides you and your kid on an easy and intuitive digital building adventure. Set contains 348 pieces.

Porsche toy car for kids:

- LEGO® Speed Champions Porsche 911 GT3 RS Super Car model kit for boys and girls aged 9 and up and Porsche fans.

1 minifigure:

- Car playset includes a Porsche driver minifigure with a helmet for kids to place behind the wheel and stage races.

Authentic Porsche details:

- LEGO® toy car features the real-life vehicle's iconic silhouette, including the rear wing, air intake features on the hood and novelty rims.

Premium Porsche model for display:

- After kids have taken the Porsche model car for a drive around the racetrack, they can display it on a shelf or bedside table.

Small gift for kids:

- This Porsche 911 model car provides a fun build-and-play experience and makes a great LEGO® gift idea for kids aged 9 and up or adult car-model collectors.

Bigger racing adventures:

- Look out for more LEGO® Speed Champions car playsets (sold separately) featuring lots of realistic details.

Iconic vehicle toys for play and display:

- LEGO® Speed Champions building sets let kids and passionate car fans build replica versions of some of the world's most famous vehicles.

Measurements:

- This 348-piece car building toy measures over 2 in. (5 cm) high, 6.5 in. (16 cm) long and 2.5 in. (7 cm) wide.

The box is black with the LEGO and Speed Champions logos in the upper left corner. The front of the box shows a yellow race car driving on a racetrack. There are green trees in the background, but they're just a blur because the car is driving so fast! The car has black trim at the bottom, and a gold and red shield logo on the front bumper. This shield is the Porsche emblem, and it has a small black horse in the center of the shield and the word PORSCHE along the top.

The top of the box shows a side view of the car, as well as a life sized image of one of the wheels.

The back of the box shows the car from a few different angles. The main image shows the back of the car as it drives through a forested mountain road. Another image shows the top of the car as it drives over a race finish line. The third image shows a picture of the real car.

Welcome to Text-Based Building Instructions from Bricks for the Blind. Here is some helpful information on how to best use screen readers and browsers: bricksfortheblind.org/help-with-screen-readers. Before you start building, here are some terms we will be using:

- In Front of/Front: towards you.
- Behind/Back: away from you.
- Up: towards the ceiling.
- Down: towards the floor.
- Stud: the bump on a LEGO brick. Example: A 2x1 brick has two studs on it.
- Vertically: with the longest side going from front to back
- Horizontally: with the longest side going from left to right.
- Upright: pointing up towards the ceiling.
- Standing upright: The piece is perpendicular to the ground, like a wall.
- Lying flat: The piece is parallel to the ground, like a piece of toast which fell off the table.
- That one/ppp: previously placed piece.
- Plate: piece with studs.
- Tile: smooth piece without studs (unless otherwise specified)
- A jumper plate is a 1x2 plate with a single stud on top, or a 1x3 plate with only two studs on top.
- "Anti-stud" is a term for the portion of a LEGO piece which accepts studs, like the bottom of a plate or brick.
- Symmetrically: a mirror image. Example: If you place a 2x1 brick with technic connector on the front wall at the right, connector to the front, and then place another such piece symmetrically on the back wall, at the right, the technic connector of the second piece should point to the back, since it will be placed symmetrically.
- Centered-vertically: even amount of space in front of and behind piece
- Centered-horizontally: even amount of space left and right of the piece.
- Row: studs lined up horizontally (left to right/side to side).
- Column: studs lined up upright or vertically (top to bottom/back to front).

For builders with low vision, or a sighted building partner who may want to follow along with the printed visual instructions that come with each kit, PDF versions are always online at LEGO.com: (<https://www.lego.com/en-us/service/building-instructions/77239>) As low vision users may benefit from viewing the instructions on a personal device where they can zoom in on content and use assistive technologies to enhance the visuals.

Sorting the pieces:

To begin a successful build, it helps to sort the pieces into groups, bags or small containers. Have a friend or family member do this in advance following the instructions below. You will see that the pieces should be sorted according to the building steps in the kit. Doing this in advance makes locating the pieces for each step easier. See below on how to sort the pieces to correspond to the steps in this set. Number the containers using letters A-Z, numbers or meaningful names. The parts will be sorted into one or a small number of steps in the instructions. Example: Steps 1-3 means collect all the parts used in steps 1, 2 and 3, and put them in one container.

This LEGO set comes with five bags labeled 1-5, a sticker sheet, and an instruction booklet. Sort the pieces into groups as described below. Note that where there are multiple colors of the same brick in a step, the colors will be split across two groups to make telling the difference easier for the builder! LEGO includes a few spare parts in case you lose something. Set these into their own group away from the rest, in case you need them later.

This build is 348 pieces, and 138 building steps.

Bag 1 (5 groups of bricks)

Minifigure Group 1 contains the pieces for the minifigure.

Main build: Porsche 911 GT3 RS

Group 1 contains the pieces for steps 1-9 of the car.

Group 2 contains the pieces for steps 10-16.

Group 3 contains the pieces for steps 17-23.

Group 4 contains the pieces for steps 24-29. Place sticker #13 for step 29.

Bag 2 (6 groups of bricks)

Group 5 contains the pieces for steps 30-35.

Group 6 contains the pieces for steps 36-40.

Group 7 contains the pieces for steps 41-44. Place sticker #3 for step 43.

Group 8 contains the pieces for steps 45-48. Place sticker #2 & #4 for step 45.

Group 9 contains the pieces for steps 49-50.

Group 10 contains the pieces for steps 51-58.

Bag 3 (5 groups of bricks)

Group 11 contains the pieces for steps 59-65.

Group 12 contains the pieces for steps 66-69, as well as a black 1x1 plate and one yellow 1x6 curved slope tile from step 70. Place stickers #6 and #11 for step 70.

Group 13 contains the rest of the pieces for step 70 and the pieces for steps 71-75.

Group 14 contains the pieces for steps 76-82. Place stickers #5 and #9 for step 79. Place sticker #10 for step 80.

Group 15 contains the pieces for steps 83-88. Place stickers #1 and #8 for step 84. Place sticker #7 for step 85.

Bag 4 (8 groups of bricks)

Group 16 contains the pieces for steps 89-94, as well as two white 1x1 bricks with a stud on one side and a rounded end on the other from step 95.

Group 17 contains the pieces for steps 95-97.

Group 18 contains the pieces for steps 98-100.

Group 19 contains the pieces for steps 101-104, as well as a yellow 1x2 curved slope tile with a sticker from step 105. Place stickers #14 and #15 for step 105.

Group 20 contains the pieces for steps 105-111.

Group 21 contains the pieces for step 112, as well as a clear 1x1 round plate from step 113. Place sticker #12.

Group 22 contains the pieces for steps 113-114, as well as a black 1x1 round plate from step 115.

Group 23 contains the pieces for step 115.

Bag 5 (6 groups of bricks)

Group 24 contains the pieces for steps 116-119.

Group 25 contains the pieces for steps 120-124.

Group 26 contains the pieces for steps 125-130.

Group 27 contains the pieces for steps 131-135.

Group 28 contains the pieces for steps 136-138.

Building Instructions:

Bag 1.

Minifigure Group: Driver

Assemble the driver minifigure by placing the torso on the legs and the head on the torso. The driver can wear a helmet, or hair. He has spiky blonde hair. Assemble the helmet by clipping a clear visor onto a white helmet. The driver wears a red driving suit and black gloves. He also has a wrench if he needs to do any maintenance!

Main Build: Porsche 911 GT3 RS Super Car

Group 1.

Step 1

Let's start building the car! We'll start with the chassis. Place a black 6x12 vehicle base, horizontally, in front of you. This piece has a 5x4 rectangle of recessed studs centered horizontally on it.

Step 2

Place a black 1x2 jumper plate, vertically, on the front two studs on the rightmost column in the recessed section of the previous piece. Place another to the left of the first. Repeat the previous two pieces symmetrically on the back side. You'll place a total of four pieces in this step.

Step 3

Place a light gray 2x4 plate, vertically and centered vertically, on the previous four pieces.

Step 4.1

Place a light gray 1x2 plate with rounded ends, vertically on the front two studs on the leftmost column in the recessed section of the chassis. Repeat symmetrically on the back side.

Step 4.2

Place the leftmost stud of a light gray 1x3 plate with rounded ends, horizontally, between the previous two pieces.

Step 5.1

Place a black 1x1 plate with a 1x1 slope tile on one side, horizontally with the slope on the right, on the left two studs on the previous piece.

Step 5.2

Place a black 1x2 jumper plate, vertically, in front of the left stud of the previous piece. Repeat symmetrically on the back side.

Step 6

Now we'll add the gear shifter! Push the bar side of a black microphone, with the ball on top, into the hollow stud to the right of the 1x1 plate with a 1x1 slope tile. This is the rightmost stud of a 1x3 plate with rounded ends.

Step 7

Place a light gray 1x2 plate with rounded ends, horizontally, on the front two studs on the rightmost two columns of the chassis. Repeat symmetrically on the back side. There should be a gap between the right two studs of these pieces.

Step 8

Place a light gray 2x6 plate, vertically and centered vertically, to the left of the previous two pieces.

Step 9.1

Place a red 1x4 tile with two studs, vertically, under the second column from the left on the chassis.

Step 9.2

Place a black 1x4 plate with a 1x1 inverted slope on each end, vertically, under the previous piece.

Group 2.

Step 10.1

Now we'll make the front axle for the car. Set the car aside for now. Place a dark gray 2x6 plate with a 1x2 brick with an axle hole on each end, vertically, in front of you.

Step 10.2

Push the axle side of a tan 1x2 axle/pin combo into the hole on the front side of the previous piece. Repeat symmetrically on the back side.

Step 11

Place a light gray 2x2 plate with studs on one side, with the side studs on the left, on the second and third rows from the front on the axle assembly. Place another behind the first.

Step 12

Place a red 1x2 grille tile, vertically and centered vertically, on the right column of the axle assembly.

Step 13

Now we'll place the axle on the chassis! Place the rest of the car, horizontally so the side with 1x2 plates with rounded ends is on the right, in front of you. Place the right column of the axle assembly, vertically with the side studs on the left, under the leftmost two studs on the chassis.

Step 14.1

Find the fifth column from the left on the chassis. This column only has three studs. Place a black 1x2 jumper plate, vertically and centered vertically, on this column. There should be one stud in front of and another behind this piece.

Step 14.2

Place a black 2x2 corner plate, with the corner at the back right so the studs form a braille letter D, in front of the previous piece so the right sides are even. Repeat symmetrically on the back side.

Step 15.1

Place a white 1x2 plate, vertically and centered vertically, between the left studs of the previous two pieces.

Step 15.2

Place a light gray 1x6 plate, vertically and centered vertically, to the left of the previous piece.

Step 15.3

Place a dark gray 1x1 plate with a stud hanging down from one side, with the side stud at the front, to the right of the front stud of the previous piece. Repeat symmetrically on the back side.

Step 16

Place a red 2x4 plate, vertically and centered vertically, on the leftmost two columns of the car.

Group 3.

Step 17

Keeping the chassis horizontal with the first axle assembly on the left, flip the car upside down. Place a white 2x4 plate with four studs hanging down from one side, upside down and vertically with the side studs on the right, centered vertically on the rightmost two columns.

Step 18.1

Place a dark gray 2x6 plate with a 1x2 brick with an axle hole on each end, upside down and vertically, on the previous piece. This will be the car's rear axle! Note that it is not at the same level as the front axle. This gives the car a slight slope down towards the front axle, which makes it look more aggressive!

Step 18.2

Push the axle side of a tan 1x2 axle/pin combo into the hole on the front side of the previous piece. Repeat symmetrically on the back side.

Step 19

Keeping the chassis horizontal, with the second axle on the right, flip the car rightside up. Place a yellow 1x2 plate with a 2x2 of studs sticking up from one side, vertically with the side studs on the right, centered vertically on the rightmost column.

Step 20

Place the right column of a light gray 2x2 tile on the previous piece.

Step 21.1

Place a black 1x2 wall panel, vertically with the wall on the right, to the left of the previous piece.

Step 21.2

Place a white 1x4 plate, vertically and centered vertically, to the left of the previous piece.

Step 21.3

Place a black 1x2 brick with a log pattern, vertically and centered vertically, to the left of the previous piece.

Step 22.1

Now we'll make an assembly that will mount the car's back window. Set the car aside for now. Place a light gray 1x4 brick, vertically, in front of you.

Step 22.2

Place a white 1x4 tile, vertically, on the previous piece.

Step 22.3

Place a light gray 1x2 plate with rounded ends, vertically and centered vertically, under the 1x4 brick.

Step 22.4

Place a white 1x1 plate with a vertical clip on one side, with the clip on the left, in front of the previous piece. Repeat symmetrically on the back side.

Step 22.5

Rotate the assembly so it lays flat, with the tile on the right and the clips on top. Place the side stud of a light gray 1x1 brick with a stud on one side, with the side stud on the right, on the front anti-stud on the left side of the assembly. Repeat symmetrically on the back side.

Step 22.6

Place the car in front of you so it is horizontal, with the side with eight side studs on the right. Find the 1x2 wall panel that is centered vertically on the third column from the right on the car. Take the assembly we just made and place it, with the tile on the right, so the 1x1 bricks with side studs are on each side of the 1x2 wall panel.

Step 23.1

Find the 1x2 brick with a log pattern that is centered vertically on the fifth column from the right. Place a black 1x1 brick with a recessed stud on one side, with the side stud at the front, in front of the 1x2 brick with a log pattern. Repeat symmetrically on the back side.

Step 23.2

Place the bottom stud of a light gray 1x1 tile with a 1x1 slope tile on one side, upright with the slope tile at the bottom, on the side stud of the front piece from the previous step. Repeat symmetrically on the back side.

Group 4.

Step 24

Find the row of seven side studs on the front side of the car. Place a black 1x6 plate with two rows of six studs sticking up from one side, horizontally with the side studs at the front, above this row of studs so the right sides are even. Repeat symmetrically on the back side.

Step 25

Place the front stud of a light gray 1x2 plate with rounded ends, vertically, on the rightmost stud of the front piece from the previous step. Repeat symmetrically on the back side.

Step 26

Place the front right stud of a black 2x2 corner plate, with the corner at the front left so the studs form a braille letter H, on the back stud of the front piece from the previous step. Repeat symmetrically on the back side.

Step 27.1

Next up, we'll start making the car's dashboard! Place a dark gray 1x4 plate, vertically, in front of you.

Step 27.2

Place a black 1x2 jumper plate, vertically on the back two studs of the previous piece. Place another in front of the first.

Step 27.3

Place a black 1x1 tile on the back piece from the previous step.

Step 27.4

Place a black 1x3 plate, vertically, under the front three studs of the dashboard assembly.

Step 27.5

Place the dashboard assembly, vertically with the previous piece at the front, on the back four studs of the fifth column from the left. This is in front of the leftmost column of three side studs on the back side of the car. There should be two free studs in front of the assembly.

Step 28.1

Find a dark gray 1x1 plate with a ring on one side. The ring has a double ended round stud attached perpendicular to the plate. Place this piece, vertically with the ring at the back, in front of you.

Step 28.2

Place a black steering wheel on the stud on the right side of the previous piece.

Step 28.3

Place a black 1x1 plate on the 1x1 plate with a ring.

Step 28.4

Place the assembly with the steering wheel in front of the dashboard assembly. This is on the front stud on the fifth column from the left on the car.

Step 29

Place a black 1x2 tile with a curved mudguard on one side, vertically with the mudguard at the front, in front of the 1x1 tile on the dashboard. This piece has a sticker with a tachometer on it.

Bag 2.

Group 5.

Step 30.1

The car should be horizontal in front of you, with the side with only four side studs on the left. Find the two rows of three studs that are to the left of the clips sticking up near the right end of the car. Place a black 1x2 slope tile, horizontally with the tall side on the left, on the left two studs of each of these two rows of studs. There should be one stud between these and the clips to the right.

Step 30.2

Place a black 1x2 plate with rounded ends, vertically, between the left studs of the previous two pieces.

Step 31.1

Next, we'll make a small assembly to mount the roof of the car. Place a light gray 1x2 brick with two studs on one side, vertically with the side studs on the right, in front of you.

Step 31.2

Place a dark gray 1x2 plate with a bar on one long side, vertically with the bar on top, on the side studs of the previous piece.

Step 31.3

Place a yellow 1x2 tile, vertically, on the previous piece.

Step 31.4

Place this assembly in the gap to the right of the 1x2 plate with rounded ends from step 30.2. The left column of the assembly should be between two 1x2 slope tiles.

Step 32

Place a black 1x2 wall panel, vertically with the wall on the right, on the 1x2 plate with rounded ends to the left of the assembly we just placed.

Step 33.1

Next, we'll add the back right wheel well. Place a yellow 2x4 mudguard, horizontally with the mudguard at the back. In front of you.

Step 33.2

Place a yellow 1x1 plate on the back left corner of the previous piece.

Step 33.3

Place the leftmost stud of a yellow 1x3 plate, horizontally, on the previous piece.

Step 33.4

Place the back stud of a yellow 1x2 plate, vertically, to the right of the previous piece.

Step 33.5

Place the front row of the wheel well assembly on the back row of the car so it overhangs one column to the right. This should be to the right of the three rows of side studs on the back side of the car.

Step 34.1

Now we'll make the front right wheel well. Place a yellow 2x4 mudguard, horizontally with the mudguard at the front. In front of you.

Step 34.2

Place a yellow 1x1 plate on the front left corner of the previous piece.

Step 34.3

Place the leftmost stud of a yellow 1x3 plate, horizontally, on the previous piece.

Step 34.4

Place the front stud of a yellow 1x2 plate, vertically, to the right of the previous piece.

Step 34.5

We'll add this wheel well assembly symmetrically to the first one. Place the back row of the fender assembly on the front row of the car so it overhangs one column to the right.

Step 35.1

Place a yellow 1x8 plate, vertically, on the rightmost column of the car. This piece will connect the two fenders.

Step 35.2

Place a black 1x2 plate with rounded ends, vertically and centered vertically, on the previous piece.

Step 35.3

Place a dark gray 1x1 round tile with a short bar on top, in front of the previous piece. Repeat symmetrically on the back side.

Group 6.

Step 36.1

Now we'll build the car's rear bumper. Set the rest of the car aside. Place a dark gray 2x4 brick, horizontally, in front of you.

Step 36.2

Place a white 2x2 plate, centered horizontally, on the previous piece.

Step 37

Place a light gray 2x3 C-shaped plate, vertically with the open side of the C on the left, to the left of the previous piece so the front sides are even. Repeat symmetrically on the right side.

Step 38

Place a yellow 1x4 plate, horizontally and centered vertically and horizontally, on the rear bumper assembly.

Step 39.1

Place a light gray 1x2 brick with two studs on one side, horizontally with the side studs at the front, centered horizontally, on the front row of the bumper assembly.

Step 39.2

Place a yellow 1x2 brick with one stud on one side, horizontally with the side stud at the front, to the left of the previous piece. Repeat symmetrically on the right side.

Step 40

Place a yellow 1x1 plate with two studs sticking up from one side, with the side studs on the left, under the front left corner of the assembly. Repeat symmetrically on the right side.

Group 7.

Step 41.1

Rotate the bumper assembly 180 degrees so the row of four side studs is at the back. Now we'll extend the bumper towards the front. Place a yellow 1x4 plate, horizontally in front of you.

Step 41.2

Place a black 1x6 plate, horizontally and centered horizontally, on the previous piece.

Step 41.3

Place a black 1x1 plate with two studs sticking up from one side, with the side studs on the left, on the leftmost stud of the previous piece. Repeat symmetrically on the right side.

Step 41.4

Place a black 1x2 plate with rounded ends, horizontally, to the right of the left piece from the previous step. Place another to the right of the first.

Step 41.5

Place this assembly under the front row on the bumper. The front row has a total of four studs, with a gap between the left two and right two. There should now be four side studs on the left and right of the assembly, and four more on the back side.

Step 42

Place a yellow 1x4 plate, horizontally and centered horizontally, on the back row of the bumper.

Step 43

Place a yellow 1x2 tile with a "GT3RS" sticker, horizontally and centered horizontally, on the previous piece.

Step 44

Place a yellow 1x2 curved slope tile, horizontally with the tall side on the right, to the left of the previous piece. Repeat symmetrically on the right side.

Group 8.

Step 45.1

Now we'll make the middle part of the bumper. Place a black 1x6 plate, horizontally, in front of you.

Step 45.2

Place a black 1x2 slope tile, horizontally with the tall side at the back, centered horizontally on the previous piece.

Step 45.3

Place a black 1x1 plate to the left of the previous piece. Repeat symmetrically on the right side.

Step 45.4

Place the right stud of a black 1x2 curved slope tile with a tail light sticker, horizontally with the tall side on the right, on the left piece from the previous step so the left side is even with the left side of the 1x6 plate. Repeat symmetrically on the right side.

Step 45.5

Place this assembly on the middle row of the main bumper assembly.

Step 46

Place a black 1x1 panel with two adjacent walls, with the walls at the back and right, on the leftmost stud on the front row of the bumper assembly. Place another to the right of the first. Repeat the previous two pieces symmetrically on the right side. You'll place a total of four pieces in this step.

Step 47

There should be a gap with two studs between the left and right pieces from the previous step. Find two black candles. A candle is a cylinder about 1.5L long that has a short bar on one side and a hole on the other side. Push the short bar of the candle into each of the two hollow studs in the gap we just found. These will be the exhaust for the car.

Step 48

Rotate the bumper assembly so the exhausts are at the bottom, with the holes at the right. There should be two rows of two side studs each on the front side of the bumper, and four studs on top. Place a yellow 1x3 plate, upright, on the left stud of each of the rows of side studs on the front side. Repeat symmetrically on the back side.

Group 9.

Step 49.1

Place the left stud of a yellow 1x2 curved slope tile, horizontally with the tall side on the left, on the top stud of the front piece from the previous step.

Step 49.2

Place a yellow 1x2 left wedged curved slope tile, horizontally with the tall side on the left and the long side on top, below the previous piece. The point should be on the right.

Step 49.3

Place a yellow 1x1 plate below the left stud of the previous piece.

Step 50.1

Place the bottom stud of a black 1x2 right wedge tile, upright with the point on top and the longest side on the left, on the previous piece.

Step 50.2

Place a black 1x1 quarter circle tile, with the flat sides on the top and left, to the right of the previous piece so the bottom sides are even.

Group 10.

Step 51.1

Now we'll do the same thing on the other side of the bumper. Rotate the bumper 180 degrees so the exhaust pipes face to the left. Find the 1x3 plate that's upright on the front side of the bumper. Place the right stud of a yellow 1x2 curved slope tile, horizontally with the tall side on the right, on the top stud of the 1x3 plate we just found.

Step 51.2

Place a yellow 1x2 right wedged curved slope tile, horizontally with the tall side on the right and the long side on top, below the previous piece. The point should be on the left.

Step 51.3

Place a yellow 1x1 plate below the right stud of the previous piece.

Step 52.1

Place the bottom stud of a black 1x2 left wedge tile, upright with the point on top and the longest side on the right, on the previous piece.

Step 52.2

Place a black 1x1 quarter circle tile, with the flat sides on the top and right, to the left of the previous piece so the bottom sides are even.

Step 53.1

Now we'll add the Porsche logo. Place a dark red 1x3 jumper plate with a Porsche print on one side, vertically, centered vertically on the middle two studs on top of the bumper. The logo should be on the left. You may want to ask a sighted friend, or use an app to get this orientation right.

Step 53.2

Find a dark red 2x2 rounded corner tile. This tile is cut out so it looks like a macaroni noodle, I'll call it a "2x2 macaroni tile" from now on. Place the left stud of this piece, with the flat sides at the back and the right, in front of the previous piece. The right side should be even with the right side of the bumper. Repeat symmetrically on the back side.

Step 54.1

Place a light gray 1x4 plate with rounded ends, vertically, in front of you.

Step 54.2

Place the right column of a yellow 2x4 plate, vertically, on the previous piece.

Step 54.3

Place the left column of the two pieces we just connected, centered vertically, on the 1x3 jumper plate from step 53.1.

Step 55

Place a black 1x1 tile on the front right stud of the 2x4 plate we just placed. Place another on the back right corner.

Step 56.1

Place a yellow 1x2 tile, vertically and centered vertically, on the left column of the 2x4 plate.

Step 56.2

Place a yellow 1x2 right wedged curved slope tile, vertically with the tall side at the back and the longest side on the right, in front of the previous piece. The point should be at the front. Repeat symmetrically on the back side with a 1x2 left wedged curved slope tile.

Step 57

Now we'll place the bumper on the car. Place the rest of the car, horizontally with the fenders on the right, in front of you. Rotate the bumper so it is vertical with the holes of the exhaust on the right. Place the bumper on the car by pushing it onto the eight side studs on the right side of the car. The bottom of the bumper should be even with the bottom of the right side of the car.

Step 58

Place a black 1x2 slope tile, horizontally with the tall side on the left, on the rightmost two studs on each of the two center rows on the car. These will attach the bumper to the rest of the car.

Bag 3.

Group 11.

Step 59.1

The car should be in front of you with the bumper on the right. Find the row of four studs above the front wheel well near the right side of the car. Place a yellow 1x3 tile, horizontally on the left three studs. Repeat symmetrically on the back side.

Step 59.2

Place a yellow 1x2 right wedge tile, horizontally with the longest side at the back and the point at the right, to the right of the front piece from the previous step. Repeat symmetrically on the back side with a 1x2 left wedge tile.

Step 60

Now we'll build the rear windows. Set the car aside for now. Place a black 1x4 plate, vertically, in front of you.

Step 61

Place the right column of a white 2x2 corner plate, with the corner at the front right so the studs form a braille letter J, under the front two studs of the previous piece. Place another symmetrically behind the first.

Step 62

Place the left stud of a transparent black 1x2 curved slope tile, horizontally with the tall side on the left, on the back right corner of the assembly. It should overhang one stud to the right. Place three more in front of the first so they cover the 1x4 plate.

Step 63

Place a black 1x4 plate, vertically, under the right studs of the previous four pieces.

Step 64

Flip the window assembly so it is upside down with the two corner plates on the right. The previous piece should be vertically on the left. Place a yellow 1x6 plate, upside down and vertically, centered vertically on the leftmost column of the assembly.

Step 65

Place a light gray 2x2 inverted curved slope tile, upside down with the tall side on the left, centered vertically on the left two columns of the assembly. The left column should be on the previous piece.

Group 12.

Step 66.1

Place the back left corner of a black 2x2 corner plate, upside down with the corner at the back left so the studs form a braille letter F, on the front anti-stud on the rightmost column of the assembly. This column only has two studs, with a gap between them. Repeat symmetrically on the back side.

Step 66.2

Place a light gray 1x2 plate with a short bar on one short side, upside down and horizontally with the bar on the left, on the back row of the front piece from the previous step. Repeat symmetrically on the back side. The window will attach to the car using these bars!

Step 67

Flip the window assembly over so it is rightside up, with the 1x6 plate vertically on the right. Place a black 1x1 plate on the front stud of the second column from the left. This column has two pairs of two studs with a gap between them. Repeat symmetrically on the back side.

Step 68.1

Now we'll add a roll bar that protects the driver if the car rolls over! Place a black 4L bar, vertically, in front of you.

Step 68.2

Push the ring of a black 1x1 plate with a ring on one side, horizontally with the ring on the left, over the front end of the previous piece. Only push it in until the bar is even with the front side of the ring. Repeat symmetrically on the back side.

Step 68.3

Place this assembly on the leftmost two studs of the window assembly.

Step 69

Place the left stud of a black 1x2 wall panel, horizontally with the wall at the front, on the front 1x1 plate with a ring from the assembly we just placed. There will be one stud in front of the right side of this piece. Repeat symmetrically on the back side.

Step 70.1

Place a yellow 1x6 curved slope tile with a curved window print, horizontally with the tall side on the left, on the front row of studs so the left side is even with the left side of the front piece from the previous step. This piece has a sticker that continues the top window on top of it.

Step 70.2

Place a black 1x1 plate under the previous piece, and between the two studs from the front row of the assembly. This is the third anti-stud from the left on the front row.

You will have a black 1x1 plate leftover when you finish this group.

Group 13.

Step 70.3

Place another yellow 1x6 curved slope tile with a curved window print symmetrically on the back row of the car. This has a corresponding window sticker for the back side of the car.

Step 70.4

Place a black 1x1 plate under the previous piece, and between the two studs from the back row of the assembly. This is the third anti-stud from the left on the back row.

Step 71.1

Place a yellow 1x1 plate under the second stud from the left on both the front and back rows of the window assembly.

Step 71.2

Place a black 1x1 plate with two studs sticking up from one side, with the side studs on the left, under each of the previous two pieces.

Step 71.3

Place a black 1x2 slope tile with a grille pattern, upright with the tall side on top, on the side studs of each of the previous two pieces.

Step 72

This piece tells you to place the stickers that should already be placed, so we'll skip it!

Step 73

Now we'll attach the rear window assembly to the car! Place the car, horizontally with the bumper on the right, in front of you. Find the two clips which extend up from the car. These are to the left of a smooth portion, and are right between the right wheel wells. Keeping the roll bar on the left, clip the two bars on the bottom of the window assembly onto the two clips we just found. The assembly will slope down to the right.

Step 74.1

Now we'll make the roof to the left of the windows. We'll do this in two parts. Place a yellow 1x2 plate, horizontally, in front of you.

Step 74.2

Place a yellow 1x1 plate on the right stud of the previous piece.

Step 74.3

Place a yellow 1x1 plate with a horizontal clip on one side, with the clip at the front, to the left of the previous piece.

Step 74.4

Place a yellow 1x2 wall panel, horizontally with the wall at the back, on the assembly.

Step 74.5

Rotate the assembly so the anti-studs are at the front and the clip is pointing down. The wall panel should be at the back with the wall on top. Find the gap to the right of the roll bar. There is another bar in this gap. Clip the assembly we just made onto this bar and push the assembly as far back as it will go.

Step 75.1

Now we'll make the rest of the roof! Place a yellow 1x2 wall panel, horizontally with the wall at the back, in front of you.

Step 75.2

Place a yellow 1x1 plate under the left stud of the previous piece.

Step 75.3

Place a yellow 1x1 plate with a horizontal clip on one side, with the clip at the front, to the right of the previous piece.

Step 75.4

Rotate the assembly so the anti-studs are at the back and the clip is pointing down. Clip it in front of the first roof assembly.

Group 14.

Step 76.1

Now we'll start working on the other side of the car! Place a white 1x1 round plate on the second stud from the front on the leftmost column of the car. Place another on the second stud from the front on the fourth column from the left. Repeat the previous two pieces symmetrically on the back side. You'll place a total of four pieces in this step.

Step 76.2

Place a yellow 1x1 plate with two studs sticking up from one side, with the side studs at the front, in front of the front right piece from the previous step. Repeat symmetrically on the back side.

Step 77

Place the front stud of a black 1x2 brick with a log pattern, vertically, on the front piece from the previous step. The back stud should attach to a 1x1 round plate. Repeat symmetrically on the back side.

Step 78.1

Now we'll build the sides of the car. Find the three rows of seven side studs on the front side of the car. Place a yellow 1x1 plate with a stud sticking up from one side, with the side stud at the bottom, on the bottom right side stud on the front side of the car.

Step 78.2

Place a yellow 1x1 plate above the previous piece.

Step 79.1

Place the bottom right stud of a yellow 2x2 right wedged curved slope tile, with the tall side on the right and the point at the bottom left, on the previous piece. This piece has a sticker showing a small black scoop, which allows air in to cool the rear brakes in the real car.

Step 79.2

Place a yellow 1x2 curved slope tile, horizontally with the tall side on the right, below the previous piece. This piece has a sticker with a black stripe on it.

Step 80

Place a yellow 1x4 tile with a sticker on it, horizontally, to the left of the previous piece. This piece has a sticker that continues the black stripe and says "GT3" on it. This sticker is directional, so you may want to ask a sighted friend for help or use an app to get the orientation right.

Step 81.1

Place a yellow 1x4 tile without a sticker, horizontally, above the previous piece and offset one stud to the left.

Step 81.2

Place a yellow 2x2 left wedge plate, with the column of studs on the left and the point at the top right, to the right of the previous piece so the top side is even with the top of the car. The right side should line up with the 2x2 wedged curved slope tile from step 79.1.

Step 82.1

Place a yellow 1x1 tile to the left of the previous piece so the top sides are even.

Step 82.2

Place a yellow 1x1 plate with a stud sticking up from one side, with the side stud on top, to the left of the previous piece. We'll mount a mirror on this piece.

Step 82.3

Place a yellow 1x1 tile to the left of the previous piece.

Group 15.

Step 83.1

Now we'll build the other side of the car! Rotate the car 180 degrees so the bumper is on the right. Find the three rows of seven side studs on the front side of the car. Place a yellow 1x1 plate with a stud sticking up from one side, with the side stud at the bottom, on the bottom left side stud on the front side of the car.

Step 83.2

Place a yellow 1x1 plate above the previous piece.

Step 84.1

Place the bottom left stud of a yellow 2x2 left wedged curved slope tile, with the tall side on the left and the point at the bottom right, on the previous piece. This piece has a sticker showing a small black scoop, just like the other side.

Step 84.2

Place a yellow 1x2 curved slope tile, horizontally with the tall side on the left, below the previous piece. This piece has a sticker with a black stripe on it.

Step 85

Place a yellow 1x4 tile with a sticker on it, horizontally, to the right of the previous piece. This piece also has a GT3 sticker on it. This sticker is directional, so you may want to ask a sighted friend for help or use an app to get the orientation right.

Step 86.1

Place a yellow 1x4 tile without a sticker, horizontally, above the previous piece and offset one stud to the right.

Step 86.2

Place a yellow 2x2 right wedge plate, with the column of studs on the right and the point at the top left, to the left of the previous piece so the top side is even with the top of the car. The right side should line up with the 2x2 wedged curved slope tile from step 84.1.

Step 87.1

Place a yellow 1x1 tile to the right of the previous piece so the top sides are even.

Step 87.2

Place a yellow 1x1 plate with a stud sticking up from one side, with the side stud on top, to the right of the previous piece. We'll mount another mirror on this piece.

Step 87.3

Place a yellow 1x1 tile to the right of the previous piece.

Step 88

Place a black 1x1 tile with one rounded end, with the rounded end on the right, on each of the two studs sticking up from the front and back sides. These are on the pieces we placed in steps 82.2 and 87.2.

Bag 4.

Group 16.

Step 89.1

Next, we'll build the car's front bumper! Set the rest of the car aside for now. Place a light gray 1x6 plate, horizontally, in front of you.

Step 89.2

Place the back row of a black 2x2 corner plate, with the corner at the back left so the studs form a braille letter F, under the left two studs of the previous piece. Repeat symmetrically on the right side.

Step 90

Place a black 1x2 plate with rounded ends, horizontally, under the 1x6 plate and between the previous two pieces.

Step 91

Place a yellow 1x1 plate on the front stud on the leftmost column of the bumper. Repeat symmetrically on the back side.

Step 92

Place a light gray 1x1 tall plate on the third stud from the left on the back row of the bumper. Place another to the right of the first.

Step 93

Place a red 1x2 plate with two studs hanging down from one side, horizontally with the side studs at the front, on the previous two pieces.

Step 94

Place a light gray 1x2 brick with two studs on one side, horizontally with the side studs at the back, on the back row of the bumper so the left sides are even. Repeat symmetrically on the right side.

You will have two white 1x1 bricks with a stud on one side and a rounded end on the other left over.

Group 17.

Step 95.1

Place a leftover white 1x1 brick with a stud on one side and a rounded end, with the side stud at the back, on the third stud from the left on the back row of the bumper. Place another to the right of first.

Step 95.2

Place a red 1x1 brick with a stud on one side and a rounded end, with the side stud at the front, to the left of the left piece from the previous step. Repeat symmetrically on the right side of the bumper.

Step 96.1

Place a yellow 1x1 plate with a 1x1 slope tile on one side, horizontally with the slope on the left, to the left of the left piece from the previous step. The left stud will overhang. Repeat symmetrically on the right side.

Step 96.2

Place a black 1x1 brick with a stud on one side, with the side stud on the left, under the left stud of the left piece from the previous step. Repeat symmetrically on the right side.

Step 97.1

Place a black 1x1 ingot tile, horizontally and centered horizontally, on the back row of the bumper.

Step 97.2

Place a black 1x2 curved slope tile, horizontally with the tall side on the right, to the left of the previous piece. Repeat symmetrically on the right side.

Group 18.

Step 98.1

Place a yellow 1x1 brick with a stud on one side, with the side stud at the front, on each of the two studs on the front row of the bumper.

Step 98.2

Place the right stud of a yellow 1x1 plate with a 1x1 slope tile on one side, horizontally with the slope on the left, on the left piece from the previous step. The left stud will overhang. Repeat symmetrically on the right side.

Step 98.3

Place a yellow 1x1 brick with a stud on one side, with the side stud at the front, under the left stud of the left piece from the previous step. Repeat symmetrically on the right side.

Step 99

Now we need to build a small sub-assembly for the bumper. Set the rest of the bumper aside for now. Place a yellow 1x4 plate, horizontally, in front of you.

Step 100

Place the side stud of a red 1x1 brick with a stud on one side and a rounded end, with the normal stud at the back and the rounded end at the bottom, under the second stud from the left of the previous piece. Place another to the right of the first.

Group 19.

Step 101

Rotate the sub-assembly so the studs of the 1x4 plate are at the front and so the studs of the previous two pieces are pointing up. Place a white 1x1 brick with a stud on one side and a rounded end, with the side stud at the front, to the left of the left piece from the previous step. Repeat symmetrically on the right side.

Step 102

Place a yellow 1x2 slope tile with a Porsche shield print, horizontally with the tall side at the back, centered horizontally on the top row of studs on the subassembly. These are the studs of the four bricks with rounded ends and side studs.

Step 103

Place a yellow 1x1 slope tile, with the tall side at the back, so the left of the previous piece. Repeat symmetrically on the back side.

Step 104

Place a yellow 1x2 tile, horizontally and centered horizontally, on the 1x4 plate on the front of the subassembly.

You will have a yellow 1x2 curved slope tile with a sticker leftover when you finish this group.

Group 20.

Step 105.1

Place the leftover yellow 1x2 curved slope tile, horizontally with the tall side on the right, to the left of the previous piece. This piece has a sticker with a turn signal printed on it.

Step 105.2

Place another 1x2 curved slope tile with a sticker symmetrically on the right side of the sub-assembly.

Step 105.3

Place a yellow 1x1 plate on the back side of the right stud of the previous piece. Repeat symmetrically on the left side.

Step 106

Now we'll add the subassembly to the rest of the bumper. Set the rest of the bumper, horizontally, in front of you so the side with the curved slope tiles is at the front and at the bottom. There should be six studs on the bottom of the bumper, eight on top, and one on each side. Place the sub assembly we just completed, horizontally with the curved slope tiles at the bottom, on the front two studs on the top side of the bumper. The curved slope tiles should be above the ones on the bumper, and should extend in front of them.

Step 107

Place a black 2x4 tile, upside down and vertically, centered horizontally under the bumper so the back side is even with the bumper assembly. The front side will stick out a little bit.

Step 108

Now we'll place the bumper on the car! Place the car, horizontally with the wheel wells on the left, in front of you. Rotate the front bumper assembly so it is vertical with the curved slope tiles on the right. Attach the bottom row of anti-studs on the left side of the bumper assembly to the four side studs on the right side of the car.

Step 109.1

Place a black 2x6 plate, horizontally and centered vertically, on the center two rows of the car, as far right as it will go. It will attach the bumper to the rest of the car.

Step 109.2

Place a black 1x2 ingot tile, vertically, on the rightmost column of the previous piece.

Step 110

Find the second column from the left of the 2x6 plate from step 109.1. Place a black 1x1 round plate on the frontmost stud on this column in front of the 2x6 plate. This is on the front row of the car. Repeat symmetrically on the back side.

Step 111

Place the back row of a white 2x3 plate, horizontally, to the left of the front stud of the 1x2 ingot tile from step 109.2. There should be a pin sticking out to the front between the left two columns of this piece. Repeat symmetrically on the back side.

Group 21.

Step 112.1

Now we'll build a small assembly. Place a yellow 1x1 plate with a stud hanging down from one side, with the side stud at the front, in front of you.

Step 112.2

Place a light gray 1x1 round tile on the previous piece.

Step 112.3

Place a yellow 1x1 plate on the side stud at the front of the assembly.

Step 112.4

Place the left stud of a yellow 1x2 curved slope tile, horizontally with the tall side at the left, on the previous piece.

Step 112.5

Find the 1x1 round plate that is on the front row, to the left of the right pin on the front side of the car. To the left of this piece are two free side studs, with a tile between them. Rotate the subassembly we just made so the round tile is at the bottom, and the anti-studs of the curved slope tiles are at the back. Place the left anti-stud of the curved slope tile on the top free side stud we found at the beginning of this step. The 1x1 round tile will sit on the 1x1 round plate on the front row of the car.

You will have a clear 1x1 round plate leftover when you finish this group.

Group 22.

Step 113.1

Now we'll make another small subassembly. Place the leftover clear 1x1 round plate in front of you.

Step 113.2

Place the left stud of a black 1x1 ingot tile, horizontally, on the previous piece.

Step 113.3

Place a black 1x1 round plate under the previous piece, to the right of the first 1x1 round plate.

Step 113.4

Place a black 1x1 plate with a stud sticking up from one side, with the side stud on the right, under the previous piece.

Step 113.5

Rotate this assembly so the ingot tile is upright at the front, and the side stud of the previous piece is at the bottom. Place this assembly on the front side of the car, under the left stud of the curved slope tile on the last subassembly we placed previously.

Step 114.1

Now we'll make these subassemblies for the other side! Rotate the car 180 degrees so the front bumper is on the left. Let's build a small assembly for this side of the car. Place a yellow 1x1 plate with a stud hanging down from one side, with the side stud at the front, in front of you.

Step 114.2

Place a light gray 1x1 round tile on the previous piece.

Step 114.3

Place a yellow 1x1 plate on the side stud at the front of the assembly.

Step 114.4

Place the right stud of a yellow 1x2 curved slope tile, horizontally with the tall side at the right, on the previous piece.

Step 114.5

We'll place this assembly symmetrically to the one from steps 112.1-112.5. Find the 1x1 round plate that is on the front row of the car, to the right of the left pin on the front side of the car. To the right of this piece are two free side studs, with a tile between them. Rotate the subassembly we just made so the round tile is at the bottom, and the anti-studs of the curved slope tiles are at the back. Place the right anti-stud of the curved slope tile on the top free side stud we found at the beginning of this step. The 1x1 round tile will sit on the 1x1 round plate on the front row of the car.

You will have a black 1x1 round plate leftover when you finish this group.

Group 23.

Step 115.1

Now we'll make another small subassembly. Place a clear 1x1 round plate in front of you.

Step 115.2

Place the left stud of a black 1x1 ingot tile, horizontally, on the previous piece.

Step 115.3

Place the leftover black 1x1 round plate under the previous piece, to the right of the first 1x1 round plate.

Step 115.4

Place a black 1x1 plate with a stud sticking up from one side, with the side stud on the right, under the previous piece.

Step 115.5

Rotate this assembly so the ingot tile is upright at the front, and the side stud of the previous piece is at the bottom. Place this assembly on the front side of the car, under the right stud of the curved slope tile on the last subassembly we placed previously.

Bag 5.

Group 24.

Step 116.1

Now we'll start on the engine bay of the car. Find the three columns of four studs near the left side of the car. Place a black 2x3 plate with one rounded end, horizontally with the rounded end on the left, centered vertically, on the left two columns. This piece goes to the right of a column of four slope tiles

Step 116.2

Place a light gray 1x4 plate, vertically and centered vertically, to the right of the previous piece.

Step 117.1

Place a black 1x3 tile, horizontally, to the left of the front stud of the previous piece. Repeat symmetrically on the back side.

Step 117.2

Place a black 1x2 plate with rounded ends, horizontally, in front of the front piece from the previous step so the left sides are even. Repeat symmetrically on the back side.

Step 118

Now we'll add a little bit of trim. Place the bottom stud of a black 1x2 left wedge tile, upright with the longest side on the right and the point at the top, on the leftmost side stud on the front side of the car. This is just to the left of the leftmost pin on the front side of the car. Repeat symmetrically on the back side with a black 1x2 right wedge tile.

Step 119

Now we'll add the wheel wells! Find the front 1x2 plate with rounded ends that we placed in step 117.2. This is in front of a 1x3 tile near the left end of the car. Place the back row of a yellow 2x2 brick with a mudguard, horizontally with the mudguard at the front, to the right of the 1x2 plate with rounded ends. Repeat symmetrically on the back side.

Group 25.

Step 120.1

Place the front row of a black 3x3 corner plate, with the corner at the front right, on the back row of the front piece from the previous step so the left stud attaches to a 1x2 plate with rounded ends. Place another symmetrically behind the first

Step 120.2

Place a yellow 1x4 plate, vertically and centered vertically, to the left of the right columns of the previous two pieces.

Step 120.3

Place a black 1x2 half circle jumper plate, vertically with the flat side on the right, centered vertically, to the left of the previous piece.

Step 121

Next, we'll add some vent details. Place a black 1x1 slope tile, with the tall side on the right, on each of the two studs on the front row of the front wheel well. These are directly behind the mudguard. Repeat symmetrically on the back side.

Step 122

Place a yellow 1x2 tile, horizontally, behind the front two pieces from the previous step. Repeat symmetrically on the back side.

Step 123.1

Place the right stud of a yellow 1x2 curved slope tile, horizontally with the tall side at the right, behind the left stud of the front piece from the previous step. Repeat symmetrically on the back side.

Step 123.2

Place a yellow 1x2 tile, vertically, between the right studs of the previous two pieces.

Step 123.3

Place a yellow 1x2 curved slope tile, horizontally with the tall side at the right, centered vertically to the left of the previous piece.

Step 124

Now we'll add the headlights! Find the two 1x1 slope tiles that are above the front left wheel well. Place a yellow 2x3 left double curved slope tile, horizontally with the longest flat side at the back, and the short flat side on the right, to the left of the two 1x1 slope tiles so the front sides are even. Repeat symmetrically on the back side with a 2x3 right double curved slope tile. These tiles are printed with a headlight pattern.

Group 26.

Step 125.1

Next, we'll finish the hood! Place a red 1x2 brick with two studs on one long side, vertically with the side studs on the left, in front of you.

Step 125.2

Place the anti-studs of a black 1x2 plate with two studs sticking up from one side, vertically with the side studs on top, on the side studs of the previous piece.

Step 125.3

Place a light gray 1x2 plate with rounded ends, vertically, on the left facing studs of the previous piece.

Step 125.4

Place the left column of a yellow 2x4 tile, vertically and centered vertically, on the right column of the assembly. This piece is printed with a small black arc on one side, this arc is part of the windshield and should be on the left. You may want to ask a sighted friend or use an app to get the orientation correct.

Step 125.5

Place the back side stud of a yellow 1x1 plate with two studs sticking up from one side, vertically with the side studs on top and the anti-stud at the back, under the front left stud of the previous piece. One side stud should extend to the front past the 2x4 tile. Repeat symmetrically on the back side.

Step 125.6

Place the right stud of a yellow 1x2 right wedge tile, horizontally with the long side at the front and the point on the left, on the front stud of the front piece from the previous step. Repeat symmetrically on the back side with a 1x2 left wedge tile.

Step 125.7

Now we'll place this assembly on the car. Rotate the assembly 180 degrees so the 2x4 tile is on the left. Find the three 1x2 curved slope tiles near the left side of the car. Place the leftmost column of the assembly on the column of four studs to the right of these curved slope tiles.

Step 126.1

Now we'll build the spoiler. Set the rest of the car aside for now. Place a black 2x6 plate, horizontally, in front of you.

Step 126.2

Place a yellow 1x2 tile, horizontally, centered horizontally on the front row of the previous piece.

Step 127

Place a black 1x1 plate with a bar on one side and a rounded end, with the bar at the front, to the left of the previous piece. Repeat symmetrically on the right side.

Step 128

Place the front stud of a black 1x2 curved slope tile, vertically with the tall side at the front, on each of the previous two pieces.

Step 129

Place a yellow 1x2 tile, horizontally, to the left of the front stud of the left piece from the previous step. This piece will overhang one stud to the left of the spoiler. Repeat symmetrically on the right side.

Step 130

Place the front stud of a black 1x2 plate with two studs sticking up from one side, vertically with the side studs at the left, under the left stud of the left piece from the previous step. Repeat symmetrically on the right side.

Group 27.

Step 131

There are three pairs of studs on the back row of the spoiler. Place a black 1x2 tile, horizontally, on each of these three pairs of studs.

Step 132

Place a black 1x2 right wedge tile, vertically with the longest side on top and the point at the front, on the side studs on the left side of the spoiler. Repeat symmetrically on the right side with a 1x2 left wedge tile.

Step 133

Find a black robot arm. This piece has a clip on one side, an angled arm, and a box with a hole on the other side. Clip this piece, with the hole facing down and the clip on top facing to the back, on the left bar on the front side of the spoiler. Repeat on the right bar.

Step 134

Now we'll add the spoiler. Place the car, horizontally with the front side on the left, in front of you. Find the two upright bars on the car near the right side. Rotate the spoiler so it is vertical with the two robot arms on the left. Push the holes on the bottom of the robot arms onto the two upright bars. Rotate the spoiler so it is parallel with the ground.

Step 135.1

Now we'll add the windshield! Place the leftmost column of a transparent black 6x6x2 windshield, vertically with the sloped side on the left, on the free column of studs on the car. The rightmost side of the window should touch the tall portion of the car.

Step 135.2

Place a yellow 2x6 tile, vertically, on the previous piece.

Group 28.

Step 136.1

Assemble four wheels by pushing a star shaped hub cap into each of the four wheels.

Step 136.2

Attach one wheel to each of the four pins on the front and back sides of the car.

Step 137

Now we'll add some more trim. Flip the car upside down, with the spoiler on the left. Find the two studs that are in between the wheels on the front row of the car. Place a black 1x8 tile, horizontally and centered horizontally, on these studs. Repeat symmetrically on the back side.

Step 138

Find the 2x4 tile that is to the right of the right pair of wheels. Place a black 3x3 plate with one rounded corner, with the rounded corner at the front left, in front of the 2x4 tile with so the left sides are even. Repeat symmetrically on the back side.

This completes the Speed Champions Porsche 911 GT3 RS Super Car.

Thank you so much for building this set!

There is one page of ads after the instructions end. This page shows ads for four LEGO Speed Champions sets. The first is for this set: set number 77239, the Speed Champions Porsche 911 GT3 RS Super Car. The second is for set number 77237, the Dodge Challenger SRT Hellcat Sports Car. The third is for set number 77238, Lamborghini Revuelto & Huracán STO. The fourth is for set number 77240, Bugatti Centodieci Hyper Sports Car.

Congratulations on finishing your build! Would you like to inspire other blind people to build LEGO sets? Let's feature your build on our [Builders page](#). It's easy and we will do all the work! Just contact us at info@bricksfortheblind.org and together we will make it happen!

Please [signup](#) for our newsletter and follow us on [Facebook](#) and [Instagram](#) to be the first to know when new instructions are available!

We hope you enjoyed building your LEGO set! Bricks for the Blind is able to create these text-based building instructions thanks to generous donations from our builders. If you enjoy the instructions we create, please consider making a \$5 donation at: <https://www.gofundme.com/f/bricks-for-the-blind-gofundme>.

Bricks for the Blind is a registered tax exempt 501(c)(3) corporation.